

CONTENTS

APRIL 2023 EDITION

FEATURES & RESOURCES

Pg 14 Dromex Globale: New Era of Workwear

Pg 18 Workwear Sizing Chart

Pg 19 Know Arc Safety

Pg 46 Poseidon 220 Protect

Pg 86 & 91 Respiratory Selection Guides

Pg 112 New Glove Standards

Pg 5	Corporate Range						
Pg 19	ARC ARC						
Pg 45	FIRE (S)						
Pg 52	Workwear						
Pg 82	Head & Face Protection						
Pg 85	Respiratory Protection						
Pg 94	Hearing Protection						
Pg 98	Safety Eyewear						
Pg 105	CUT ⁵						
Pg 111	Specialised Gloves						
Pg 124	Working Gloves						
Pg 131	Body Protection						
Pg 147	Fall Arrest, Reflective Wear						

& Support

Footwear

Pg 157





KNOW SAFETY. NO INJURY. KNOW DROMEX.

Dromex is Africa's leading PPE & Workwear wholesaler dedicated to supplying quality protective products and workwear to employers and workers throughout industries around the world.

Originally founded as Industrial & Marine Sealing Systems (IMSS) in 1998 by our CEO, Stel Stylianou and operating from a 750m² warehouse, the Dromex range was strategically developed and has grown into one of South Africa's most trusted PPE brands.

Our warehouse capacity now stands over 45 000m² with modern receiving & dispatch facilities at our New Germany premises and ensures that we have large volumes of internationally accredited PPE & Workwear in stock at all times and promptly dispatch in both quality & quantity.

As active members of various SABS technical committees, a member of SAPEMA and SAIOSH you can be assured that our PPE & Workwear comply with local industry standards and regulations.

Our PPE Specialists are continually up to date with the latest EN, ANSI, NFPA and additional international standards and are equipped to advise you on PPE & Workwear that is fit-forpurpose to keep the men & women who rely on protective equipment and clothing as comfortable & safe as possible.

OUALITY STANDARDS

We carefully select our suppliers, which ensures that we import products certified to international standards from ISO accredited companies around the world.

SERVICE

Our service and fiercely competitive pricing strategies result in often unparalleled levels of value for money and drive our quality PPE products through a loyal group of large and medium distributors throughout South Africa and Africa.

ADVICE & TRAINING

With extensive experience in various fields requiring PPE, we're able to provide on-site PPE evaluations, advice and training. Technical back up and distributor training is available at Dromex support centres in Durban, Johannesburg, Cape Town & Richards Bay.

INNOVATION

New Products and innovations are continually being added to our range, and quality is reviewed on an on-going basis ensuring we offer the best possible specialist services to meet the ever changing demands of the PPE market.

We believe that all employees in any work environment are entitled to maximum safety protection and that employers should not have to compromise on the quality of the PPE products they provide for their staff.

DROMEX KZN HEAD OFFICE

Unit 1, 1 Blase Road, New Germany, 3620, South Africa **T.** +27 (0)31 713 1960 **F.** +27 (0)31 705 6508 **E-Fax.** 0866 844 595 sales@dromex.co.za | www.dromex.co.za | 0861 DROMEX





EVERY WEAR CORPORATE CLOTHING RANGE






The all new Dromex corporate clothing range will take you from the office to the golf course and is equally perfect for administrative, promotional, warehouse and delivery personnel.

We've ensured quality in every detail - every cotton thread, every button, every metre of fabric has been meticulously chosen with the user in mind to provide comfort & value.

Manufactured with the latest technology in pattern making, cutting & sewing automation, we are able to provide consistency in our clothing fit & durability.

We're committed to supplying quality without compromise and this promise is at the forefront of every Dromex garment.





Available colours:





Available t-shirt colours:



White Grey Yellow Green Red Royal Blue Navy Black



Available colours:











White Stone Sky Blue Navy Black




Available colours:











- Two front pockets, money pocket & two back pockets
- The natural fibres make this garment comfortable & breathable
- Suitable for casual & smart/casual use

Sizes: 26 - 50





FOR THOSE WHO WORK BEYOND THE ORDINARY

We know what it's like to face the deafening silence of 100 000 volts. How it feels to be one step away from danger every day. That is why Dromex believes that all employees are entitled to maximum protection without compromise.

From essential PPE to our state-of-the-art ARC protection, it is our responsibility to supply products that will deliver on this promise.

And it's not something we take lightly.





NEWS

DROMEX GLOBALE: THE NEW ERA OF WORKWEAR

At Dromex we're committed to providing customers with only the best PPE and Workwear, and this means we're always looking at new ways of improving our range.

To achieve our goal of being Africa's premier PPE supplier, we've built our own 8000m² state-of-the-art manufacturing facility at the new intermodal Keystone Park hub in Hammarsdale to ensure we deliver on that promise.

Dromex Globale is an SABS approved facility, dedicated to manufacturing all Dromex workwear at competitive prices with uncompromising quality, conforming to the highest standards.

Our workwear factory is BBBEE Certified and successfully provided 500 jobs at commencement with an additional 600 jobs within the following 18-36 months.

The in-house training facility endeavours to upskill the youth of Hammarsdale resulting in an empowered workforce.

Designed with the stringent needs of local and international markets in mind, Dromex Globale will change the way we supply workwear.

THE FUTURE OF PPE BEGINS TODAY

Dromex believes that all employees are entitled to maximum protection and that employers should never have to compromise on the quality of the personal protective products they supply their staff.

And with our new Dromex Globale manufacturing facility, you can be sure you're dealing with a company that puts safety first.













SABS is a statutory body that was established in terms of the Standards Act. These standards, SANS (South African National Standards) promote quality in connection with commodities, products and services. SABS mark bearing products are made under a permit from the SABS for specific products made to SANS standards by a registered manufacturer and include quality audits and verification.

SANS 434: This standard specifies requirements for the material, cut, make and trim of boilersuits, two-piece workwear suits, bib and brace overalls and coats and jackets (unlined) but does not cover garments designed for the protection against specific hazards. This covers the materials, workmanship, styles, sizes, makeup of the suits, stitches & seams.

SANS 1387: South African National Standard woven cotton and similar apparel fabrics. This covers 11 types of fabric, however the parts 1 to 4 are relevant to the workwear.

Part 4 is for cotton iean and drill fabrics.

J54 - Jean material with a 2/1 twill weave, 220g/m² minimum.

D59 - Drill material with a 4/1 satin weave, 270/m² minimum.

SANS 1423: Part 1 is for performance requirements for textile fabrics of low flammability. The standard covers the flammability performance requirements for four classes of washable apparel fabric, each class being divided into three flammability performance categories. NOTE The use of certain fabric combinations, trims, accessories and sewing threads that are not compatible can have an adverse effect on the flammability performance of a garment.

Fabric Class:

Class A: Capable of withstanding the required industrial or hospital laundry processes given in SANS 10146

Class B: Capable of withstanding wash treatments at temperatures of up to 95 °C

Class C: Capable of withstanding wash treatments at temperatures of up to 60 °C

Class D: Capable of withstanding wash treatments at temperatures of up to 40 °C

Flammability Category:

Category 1: The fabric does not ignite within a given time period.

Category 2: The fabric ignites within a given time period but the flame spread ceases within a specified distance.

Category 3: The fabric ignites within a given time period and might continue to flame but at a rate of flame propagation that is within a specified limit.

SANS 724: Personal Protective Equipment & Protective Clothing against thermal hazards of an electric Arc.

Design, selection and performance requirements of electric arc resistant clothing and equipment for the protection of persons against the thermal hazards of an electric arc, which could occur during operating or working on or near electrical equipment in the workplace.

SANS 61482 Live working, Protective clothing, against the thermal hazards of an electric arc. Part 1 is IEC 61482-1-1 determination of the arc rating (ATPV or EBT50) of flame resistant materials for clothing. IEC 61482-1-1 Method A is identical to ASTM F1959, with the exception of different laundry preconditioning requirements.

SANS 50471 EN 471 High-visibility warning clothing for professional use - test methods and requirements.

NFPA: The NFPA (National Fire Protection Association) is a United States trade association, albeit with some international members, that creates and maintains private, copyrighted standards and codes for usage and adoption by local governments.

NFPA 1975 Provisions apply to design, performance, testing and certification of non-primary protective work apparel and the individual garments comprising work apparel.

Specifies criteria for thermally stable textiles that will not rapidly deteriorate, melt, shrink, or adhere to the wearer's skin, and also provides optional requirements and tests to verify flame resistance, odour resistance, water resistance and insect repellancy.

NFPA 70E Safe work practices to protect personnel by reducing exposure to major electrical hazards. NFPA 70E helps companies and employees avoid work-place injuries and fatalities due to shock, electrocution, arc flash, and arc blast.

The Standard includes guidance for making hazard identification and risk assessments, selecting appropriate PPE, establishing an electrically safe work condition and employee training.

NFPA 2112 This standard protects workers from flash fire exposure and injury by specifying performance requirements and test methods for flame-resistant fabric and garments. Criteria cover design, construction, evaluation and certification of flame-resistant garments for use by industrial personnel, with the intent of not contributing to the burn injury of the wearer, providing a degree of protection to the wearer and reducing the severity of burn injuries resulting from short-duration thermal exposures resulting from accidental exposure to flash fires.

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies, ISO member bodies. International Standards are carried out through ISO technical committees and each member of the body has the right to be represented.

ISO 13688 This International Standard specifies general performance requirements for ergonomics, innocuousness, size designation, ageing, compatibility and marking of protective clothing and the information to be supplied by the manufacturer with the protective clothing. This International Standard is only intended to be used in combination with other standards containing requirements for specific protective performance and not on a stand-alone basis.

ISO 6530 This International Standard specifies a test method for the measurement of indices of penetration, absorption and repellence for protective clothing materials against liquid chemicals, mainly chemicals of low volatility. Two levels of the potential performance of materials are assessed by this method of testing to meet with possible requirements for protection against:


a) deposition on the surface of a material, at minimal pressure, of spray droplets up to coalescence or occasional small drips;

b) contamination by a single low-volume splash or low-pressure jet, allowing sufficient time to divest the clothing or take other action as necessary to eliminate any hazard to the wearer from chemical retained by the protective garment, or, in circumstances where pressure is applied to liquid contaminants on the surface of the clothing material, as a result of natural movements of the wearer (flexing of contaminated areas of clothing at arms, knees, shoulders) and contact with contaminated surfaces (e.g. walking through sprayed foliage). The tested chemicals for the South African market are: HNO3 (Nitric Acid), HCI (Hydrochloric Acid), H2SO4 (Sulphuric Acid) and NaOH (Sodium Hydroxide).



DROMEX WORKWEAR SIZING CHART

ALPHA NUMERIC	SABS SANS 434	CHEST CIRCUMFERENCE	LONG SLEEVES		WAIST EXTENDED	OUTSIDELEG	INLEG	ЕХЕСИПVЕ РІТ	CHEST SIZE	BACK LENGTH	SLEEVE LENGTH	BACKWIDTH		WAIST EXTENDED	OUTSIDE LEG	INLEG	СОМЕГЕТ	CHEST SIZE	BACK LENGTH	SLEEVE LENGTH	BACKWIDTH		WAIST EXTENDED	OUTSIDE LEG	
	ĕ	æ	Ę	7	E	£	E) S	E	E	u U	E G	7	E	E	E	, m	E	E	ŧ	E	Ã	<u>۔</u> ق		┸
XS	30/77	94	47	26/67	80	102	78	30/77	95	29	49	36	79/92	75	94	20	30/77	92	64	43	41	26/67	72	96.5	+
S	32/82	66	47	28/72	85	104	79	32/82	100	89	49	38	28/72	80	96	71	32/82	- 26	64.5	43	42.5	28/72	77	97.5	; !
	34/87	104	48	30/77	8	106	8	34/87	105	69	20	40	30/77	85	86	71	34/87	102	65	43	45.05	30/77	82	98.5	
2	36/92	109	48	32/82	95	108	81	36/92	110	20	20	42	32/82	06	100	72	36/92	107	65.5	4	45.5	32/82	87	100	:
Z.	38/97	114	49	34/87	100	110	82	38/97	115	11	51	44	34/87	56	102	73	38/97	112	89	45	47	34/87	92	101	:
	40/102	119	49	36/92	105	110	82	40/102	120	72	51	46	36/92	100	102	74	40/102	117	68.5	45	48.5	36/92	6	102.5	· · ·
_	42/107	124	20	38/97	110	111	82	42/107	125	73	52	48	38/97	105	103	74	42/107	122	69	45	20	38/97	102	103.5	1
	44/112	129	20	40/102	115	111	82	44/112	130	73	52	20	40/102	110	103	74	44/112	127	70.5	45	51.5	40/102	107	105	
۸L	46/117	134	51	42/107	120	111	81	46/117	135	74	53	52	42/107	115	103	73	46/117	132	72	46	53	42/107	112	106	
_	48/122	139	51	44/112	125	111	81	48/122	140	74	53	54	44/112	120	103	73	48/122	137	73.5	47	55	44/112	117	107.5	
ZXL	50/127	144	52	46/117	130	111	80	50/127	145	75	54	26	46/117	125	103	72	50/127	142	75	48	26	46/117	122	108.5	-
	52/132	149	52	48/122	135	111	80	, 52/132	150	75	54	28	48/122	130	103	72	52/132	147	76.5	49	57.5	, 48/122	127	110	_
3XL	54/137	154	53	50/127	140	112	80	54/137	155	92	22	09	50/127	135	104	72	54/137	152	77	49	59	50/127	132	111	:
7	56/142	159	53	52/132	145	112	8	56/142	160	92	22	62	52/132	140	104	72	56/142	157	77.5	49	60.5	52/132	137	112.5	!
4XL	58/147	164	54	54/137	150	113	80	58/147	165	77	99	64	54/137	145	105	72	58/147	162	78	20	62	54/137	142	113.5	
.,	60/152	169	54	56/142	155	113	80	60/152	170	77	26	99	56/142	150	106	72	60/152	167	78.5	20	63.5	56/142	152	114.5	-
2XL	62/157	174	54	58/147	160	113	80	62/157	175	78	57	89	58/147	155	106	72	62/157	172	79	20	92	58/147	157	115.5	
9	64/162	179	54	60/152	165	114	80	64/162	180	78	22	0/	60/152	160	106	72	64/162	177	79.5	20	66.5	60/152	162	116.5	
exF	66/167		Щ	62/157	170	Щ	<u> </u>	1	_	_	_			_	_	_	1	_	_	_	_		_	_	-





INNOVATION

INTRODUCING THE DROMEX ARC RANGE

Through years of consulting with experts, testing fabric combinations and working with world-leading testing facilities, we are proud to bring the Dromex ARC range of workwear and PPE to the global stage.

Dromex is committed to developing quality products, that effectively mitigate risk, which extends to our specialist offering - specifically our ARC range which has been designed to reduce the risks associated with hazardous industries, where 2nd & 3rd degree burns can occur.

Our ARC workwear is manufactured locally using our custom Dromex A.P.T™ (Arc Protection Technologies) fabric and is certified to the highest local and international standards.

Each garment is rated to varying degrees for specific environments and conditions and our ARC range includes a number of styles and accessories for various industries.

Dromex ARC workwear and PPE is suitable during any work with or within the vicinity of industrial electrical panels switch rooms, substations and utilities power generators.

THE SAFETY IS IN THE DETAIL

When it comes to safety, the smallest detail can make a difference. Through extensive research, development, and testing, we've created an ARC range that's every bit as comfortable and practical as it is safe:

- $\cdot \ \ Inherent \ flame\text{-retardant thread}$
- · Triple needle stitched seams
- · Transfer print & embroidery logos
- · Flame-retardant Velcro
- · Double needle stitched FR reflective tape







MEETING THE HIGHEST STANDARDS

Dromex believes in uncompromising safety, so we've insisted that the integrity of our specialist ARC range also passes the most stringent garment tests in addition to the fabric tests.

We're proud to be associated with the leading standards authorities locally and internationally enabling us to produce certified ARC workwear.

These standards include:

- · IEC 61482-1-1 · IEC 61482-1-2 · NFPA 70E · NFPA 2112
- · SANS 724 · ASTM F1959 · ASTM F2621-12
- · EN 11611:2015 · EN 11612:2015 · EN 61482-1-2:2014


















EN

At Dromex we believe that all employees are entitled to maximum safety protection and that employers should never have to compromise on the quality of protective equipment they supply their staff.

Our Arc range ensures that we deliver on that promise.






FABRIC TESTING vs GARMENT TESTING



Arc fabric & garment tests are vital to ensure that both FR fabrics and the constructed garment pass the necessary international requirements for Arc Workwear and ultimately worker safety.

Arc fabric testing is done first to ensure that the fabric passes the required ratings & quality standards.

Thereafter the Arc garment is fully constructed using the certified fabric mannequin tested to ensure performance & appropriate protection.



IMPORTANT: Always request a *FABRIC TEST* report & certificate in addition to the *GARMENT INTEGRITY TEST*.

A reputable supplier should be able to produce BOTH certificates upon request.



UNDERSTANDING ARC WORKWEAR

FR COTTON vs INHERENT FABRICS

> FLAME RETARDANT COTTON FABRICS:

FR Cotton fabrics have had flame retardants engineered into the fabric to create flame resistance thereby producing fabrics that have guaranteed flame retardancy for the life of the garment.

> INHERENT FLAME RETARDANT FABRICS:

'Inherent fabrics' consist of synthetic fibre that do not require additional FR chemical treatments each fibre is 'inherently' flame retardant.

All FR fabrics (inherent & treated) are engineered to prevent ignition. While the fabrics are essentially different, technological advancements and development means that the efficacy of both fabrics are very similar and choosing Arc workwear should be based on:

- Arc hazard & environment of use
- Performance & certifications
- Comfort & quality
- Durability
- Value & availability
- Brand reputation

Sample(s) Received:

Did You Know?

Dromex A.P.T™ FR Cotton Fabric has passed "Red Metal" testing which offers additional bodily protection from molten metal, vaporised copper & metal oxides up to 1400°C. This offers the wearer effective protection and peace of mind.

Molten metal is a deadly hazard that can easily penetrate synthetic lightweight fabrics during an Arc Flash incident.

..

ArcWear

Dromex 1 Blasé Road, New Germany Durban, KZN South Africa 3620

300til Anina 3020 Dromex, Style Dromex A.P.T., 9.0 ozlyd² 305 g/m² Wc Navy, AAD 9.7 ozlyd² 329 g/m², ArcWear# 1911P05 12/6/2019

12/12/2019

Testing Date:

Testing was completed in accordance with the method identified below at ArcWear in ouisville, Kentucky.

Test Report: 1911P05-X

When a garment is tested for flammability against the NFPA 2112 standard it has already been washed 100 times before NFPA 2112 tests are applied.

> At Dromex we believed in the superior quality of our fabric and took this test one step further.

FLAMMABILITY TESTING

Our Dromex A.P.T™ fabric was tested against the NFPA 2112 standard and passed after 200 washes.

		AST	M D3776/D377	76M								
Standard T	est Method f	or Mass per	Unit Area Fal	oric Weight-C	ption C Smal	I Swatch						
Precondi	tioning:		200 cycles of 18	200 cycles of washing and drying as specified in sec 8.1.3 of NFPA 2112-								
Condition	oning:			ASTM D1776								
Slevages I	ncluded:				No							
Fabric Mass	s (oz/vd²):				10.18							
Fabric Mas	is (a/m²):				345							
T dono mad	(g/111).	ASTN	D6413/D6413	M-15	0.10							
Star	ndard Test M	ethod for FI	ame Resistan	ce of Textiles	(Vertical Tes	t)						
Precondi			200 cycles of washing and drying as specified in sec 8.1.3 of NFPA 2112-18									
		L	ength Direction									
	1	2	3	4	5	AVG Length						
Afterflame Time (sec)	0.2	0.2	0.0	0.0	0.0	0.1						
Afterglow Time (sec)	1.0	1.0	1.2	1.2	1.0	1.1						
Char Length (mm)	78	78	72	75	81	77						
Melting?	No	No	No	No	No							
Dripping?	No	No	No	No	No							
			Width Direction									
	1	2	3	4	5	AVG Width						
Afterflame Time (sec)	0.2	0.2	0.0	0.0	0.0	0.1						
Afterglow Time (sec)	1.2	1.4	1.0	1.0	1.4	1.2						
Char Length (mm)	61	75	78	72	78	73						
Melting?	No	No	No	No	No							
Dripping?	No	No	No	No	No							

Kirby
Date: 2019.12.12 09:22:11
-05'00'
in full, without written approval

ARC WORKWEAR LIFESPAN

The lifespan of an Arc garment is dependent on many factors such as wash care, storage between use and wear and tear during use.

E.g. If the garment has been in use for 3 weeks and a worker is exposed to an Arc Flash incident the workwear and PPE needs to be replaced therefore the lifesan of the garment has ended. Likewise if Arc workwear & PPE is damaged during use, it needs to be removed from service and replaced immediately.



ARC THERMAL PROTECTION VALUE

ATPV is the embroidered or printed markings on all Arc workwear & PPE.

ATPV is measured in cal/cm² and is defined as the maximum incident heat energy that a fabric can absorb and lessen the injury against a 2nd or 3rd degree burn.

For example, if a worker has the potential to be exposed to an incident where the heat energy level is less than 4.0 cal/cm², the required ATPV clothing & PPE is a minimum of 4 cal/cm².





HEAT ATTENUATION FACTOR (HAF)

HAF refers to the amount of heat blocked by the FR fabric. Though a fabric may be flame resistant, it may not block all of the heat to which it is exposed. An HAF of 85% means that it will block 85% of the heat the fabric encounters. This applies to a short burst of heat - usually less than one second. In the event of prolonged heat exposure, the HAF would be lower.

Note: Synthetic fabrics generally have a lower HAF than Cotton FR Fabrics.

ARC WORKWEAR & PPE SELECTION

HAZARD / RISK CATEGORY	CLOTHING DESCRIPTION RECOMMENDED	MINIMUM REQUIRED ARC RATING OF PPE CAL/CM ²
1 HRC	Arc Rated FR shirt & FR pants or coverall	4
HRC	Arc Rated FR shirt & FR pants or coverall	8
HRC	Arc rated FR shirt or FR pants or FR coverall and arc flash suit selected so that the system arc rating meets the required minimum	25
HRC	Arc rated FR shirt or FR pants or FR coverall and arc flash suit selected so that the system arc rating meets the required minimum	40

NOTE: Energy / Incident Analysis & Calculation assessments are available on request to ensure correct Arc Workwear & PPE selection according to the arc hazard present.





100CAL ARC SUIT BIB & BRACE, JACKET & HOOD













OEKO-TEX®

CODES: DW-ARC100-J / BP (JACKET / BIP PANTS)

DH-ARC100-SH (SWITCHING HOOD) DG-ARC100 (SWITCHING GLOVE)

DH-ARC100-KIT (JACKET/PANTS/VENTILATED HOOD, GLOVES)

NFPA 2112, NFPA 70E, SANS 724, ASTM F2621-12, EN 11612:2015, EN 61482-2-2:2020 HOOD: ASTM F2178-12 GLOVE: ASTM F2675

- ATPV 100cal/cm²
- Dromex A.P.T Fabric 88% Cotton, 12% Nylon
- Triple layer construction: 14oz outer, 250gsm meta aramid FR mat lining & 14oz inner
- Inherent flame retardant thread throughout
- Fully triple needle stitched garment
- Concealed YKK Vizlon zip on jacket
- Flame retardant hook & loop closures
- Flame retardant knitted rib cuffing
- cal/cm² Rating embroidery on hood, jacket, bib & brace and gloves

Hood:

- Back flap with hook & loop closure for built-in fan/air system
- Flame retardant hook & loop closures
- Dromex BSD 100cal/cm² Arc Visor with Real View Technology
- Integrated fresh air arc flash ventilation system for cooling

Sizes:

Jackets: S-5XL Bib & Brace: S - 5XL

Gloves: S/M & L/XL (see pg 40 for more info)

- Substations & switchrooms
- **Utilities & power generators**
- Industrial electrical maintenance & installations
- Mining, chemical & refineries



55CAL ARC SUIT BIB & BRACE, JACKET & HOOD

CODES: DW-ARC55-J / BP (JACKET / BIB PANTS)

DH-ARC55-SH (SWITCHING HOOD)

DH-ARC55-SHV (SWITHING HOOD WITH VENTILATION)















IEC 61482-1-1, NFPA 2112, NFPA 70E, SANS 724, ASTM F1959, ASTM F2621-12, EN 11612:2015 HOOD: ASTM F2178-12

- ATPV 55cal/cm²
- Dromex A.P.T Fabric 88% Cotton, 12% Nylon
- · Double layer construction: 14oz & 9oz inner
- Inherent flame retardant thread throughout
- Fully triple needle stitched garment
- YKK Concealed brass zips on jackets
- Flame retardant hook & loop closures
- · Flame retardant knitted rib cuffing
- cal/cm² Rating embroidery on hood, jacket, bib & brace

Hood:

- · Back flap with hook & loop closure for built-in fan/air system
- Flame retardant hook & loop closures throughout
- Dromex BSD Arc Visor with Real View Technology
- · Available with or without ventilation

Sizes:

- Jackets: S 5XL
- Bib & Brace: S 5XL

- Substations & switchrooms
- Utilities & power generators
- Industrial electrical maintenance & installations
- Mining, chemical & refineries







25CAL ARC SUIT

CODE: DW-ARC25-J/P













OEKO-TEX®

IEC 61482-1-1, NFPA 2112, NFPA 70E, SANS 724, ASTM F1959, ASTM F2621-12, ASTM 1506-19, EN 11612:2015

- ATPV 25cal/cm²
- 14oz Dromex A.P.T Fabric 88% Cotton, 12% Nylon
- Flame retardant thread throughout
- YKK Concealed brass zips on jacket & pants
- Flame retardnt hook & loop closures
- Fully triple needle topstitched garment
- Flame retardant knitted rib cuffing
- Three jacket pockets with mitred flap & flame retardant hook & loop closure & side swing pocket on pants
- cal/cm² Rating embroidery on jacket & pants

Sizes:

Jackets: S - 5XL Pants: S-5XL

- Substations & switchrooms
- Utilities & power generators
- Industrial electrical maintenance & installations
- Mining, chemical & refineries



15CAL ARC SUIT

CODE: DW-ARC15-J / P













OEKO-TEX®

IEC 61482-1-1, IEC 61482-1-2, NFPA 2112, NFPA 70E, SANS 724, ASTM F1959, ASTM F2621-12, EN 11611:2015, EN 11612:2015, EN 61482-1-2:2014, CE 0338:2016

- ATPV 15cal/cm²
- Dromex A.P.T Fabric 88% Cotton 12% Nylon, 305gsm
- Flame retardant thread throughout
- YKK concealed brass zip on jacket & pants
- Flame retardant hook & loop closures
- · Full triple needle topstitched garment
- · Flame retardant knitted rib cuffing
- Three jacket pockets with mitred flap & flame retardant hook & loop closure & side swing pockets on pants
- 50mm Flame retardant reflective tape on arms & legs
- cal/cm² Rating embroidery on jacket & pants

Sizes:

• Jackets: 30 - 68 • Pants: 28 - 66

- · Substations & switchrooms
- Utilities & power generators
- Industrial electrical maintenance & installations
- Mining, chemical & refineries







12.4CAL ARC SUIT*

CODE: DW-ARC12-OR















IEC 61482-1-1, IEC 61482-1-2, NFPA 2112, NFPA 70E, SANS 724, ASTM F1959, ASTM F2621-12, EN 11611:2015, EN 11612:2015, EN 61482-1-2:2014, CE 0338:2016

- ATPV 12.4 cal/cm² *Tested & approved up to 15 cal/cm²
- Dromex A.P.T Fabric 88% Cotton 12% Nylon, 305gsm
- Flame retardant thread throughout
- YKK concealed brass zip on jacket & pants
- Flame retardant hook & loop closures
- Full triple needle topstitched garment
- · Flame retardant knitted rib cuffing
- Three jacket pockets with mitred flap & flame retardant hook & loop closure & side swing pockets on pants
- 50mm Flame retardant reflective tape on arms & legs
- cal/cm² Rating embroidery on jacket & pants

Sizes:

• Jackets: 32 - 60 • Pants: 28 - 56

- · Substations & switchrooms
- Utilities & power generators
- Industrial electrical maintenance & installations
- · Mining, chemical & refineries



15CAL ARC BOILERSUIT

CODE: DW-ARC15-O















IEC 61482-1-1, IEC 61482-1-2, NFPA 2112, NFPA 70E, SANS 724, ASTM F1959, ASTM F2621-12, EN 11611:2015, EN 11612:2015, EN 61482-1-2:2014, CE 0338:2016

- ATPV 15 cal/cm²
- Dromex A.P.T Fabric 88% Cotton 12% Nylon, 305gsm
- Flame retardant thread throughout
- YKK concealed brass zip
- Flame retardant hook & loop closures
- · Triple needle topstitched garment
- · Flame retardant knitted rib cuffing
- Two breast pockets with mitred flap & flame retardant hook & loop closure & side entry hip pockets
- 50mm Flame retardant reflective tape on arms, legs & "X" on back
- cal/cm² Rating embroidery on right breast pocket flap

Sizes: 30 - 64

- · Substations & switchrooms
- Utilities & power generators
- · Industrial electrical maintenance & installations
- · Mining, chemical & refineries





LADIES 15CAL ARC SUIT

CODE: DWL-ARC15-J / P











IEC 61482-1-1, IEC 61482-1-2, NFPA 2112, NFPA 70E, SANS 724, ASTM F1959, ASTM F2621-12, EN 11611:2015, EN 11612:2015, EN 61482-1-2:2014

- ATPV 15cal/cm²
- Dromex A.P.T Fabric 88% Cotton, 12% Nylon, 305gsm
- Full triple needle topstitched garment
- Flame retardant thread throughout
- YKK Concealed brass zips on jackets & pants
- Flame retardant hook & loop closures
- Flame retardant knitted rib cuffing
- Three jacket pockets with mitred flap & flame retardant hook & loop closure & side swing pockets on pants
- cal/cm² Rating embroidery on jacket & pants
- 50mm Flame retardant reflective tape on arms & legs

Sizes: S-5XL

- Substations & switchrooms
- Utilities & power generators
- Industrial electrical maintenance & installations
- Mining, chemical & refineries





15CAL ARC SHIRT

CODE: DW-ARC15-S











OEKO-TEX®

IEC 61482-1-1, IEC 61482-1-2, NFPA 2112, NFPA 70E, ASTM F1959, ASTM F2621-12, EN 11611:2015, EN 61482-1-1:2009 EN 11612:2015, EN 61482-2:2009, CE 0338:2016

- ATPV 15 cal/cm²
- Dromex A.P.T Fabric 88% Cotton 12% Nylon, 305gsm
- · Flame retardant thread throughout
- Flame retardant melamine buttons
- Triple needle topstitched garment
- Two mitred breast pockets with double needle topstitching & mitred flap
- 50mm Lime/silver/lime FR reflective tape
- cal/cm² Rating embroidery on right breast

S - 5XL Sizes:

- Substations & switchrooms
- Utilities & power generators
- Industrial electrical maintenance & installations
- Mining, chemical & refineries







9.6CAL ARC SHIRT

CODE: DW-ARC9,6











OEKO-TEX®

IEC 61482-1-2, NFPA 2112, NFPA 70E, ASTM F2621-12, EN 11611:2015, EN 11612:2015

- ATPV 9.6 cal/cm²
- Dromex A.P.T Fabric 88% Cotton 12% Nylon, 237gsm
- · Flame retardant thread throughout
- Flame retardant melamine buttons
- Triple needle topstitched garment
- Two mitred breast pockets with double needle topstitching & mitred flap
- 50mm silver FR reflective tape
- cal/cm² Rating embroidery on right breast

Sizes: S - 5XL

- Substations & switchrooms
- Utilities & power generators
- Industrial electrical maintenance & installations
- · Mining, chemical & refineries



40CAL ARC THERMAL JACKET

CODE: DW-ARC40-WJ















NFPA 2112, EN 11611:2015, EN 11612:2015

- ATPV 40 cal/cm²
- Dromex A.P.T Fabric 88% Cotton 12% Nylon, 305gsm (Outer fabric & lining)
- · Flame retardant wadding interlining
- · Flame retardant thread throughout
- Flame retardant hook & loop closure on pockets & front
- Flame retardant rib knit cuffing on sleeves
- cal/cm² Rating embroidery on right breast
- 50mm Flame retardant reflective tape on arms
- Double needle topstitching on armholes & shoulders
- · Rounded chest pocket and mitred flap with FR hook & loop closure
- Concealed YKK chunky nylon zip with 25mm FR hook & loop closure

Sizes: XS - 5XL

- Substations & switchrooms
- Utilities & power generators
- · Industrial electrical maintenance & installations
- · Mining, chemical & refineries







15CAL ARC X-BIB

CODE: DW-ARCXBIB12.4









OEKO-TEX®

IEC 61482-1-2, NFPA 2112, NFPA 70E, ASTM F1959, EN 11611:2015, EN 11612:2015, EN 61482-1-2:2014, EN ISO 20471:2013

- ATPV 15 cal/cm²
- Dromex A.P.T Fabric 88% Cotton 12% Nylon, 305gsm
- Flame retardant thread throughout
- Adjustable flame retardant hook & loop closure
- 50mm Lime/silver/lime flame retardant reflective tape

S-XL Sizes: 2XL - 5XL

- Substations & switchrooms
- Utilities & power generators
- Industrial electrical maintenance & installations
- Mining, chemical & refineries





21CAL ARC DENIM JEANS

CODE: DW-ARC21-DJ















NFPA 2112, NFPA 70E, ASTM F1959, EN 11611:2015, EN 11612:2015, EN 61482-1-2:2014

- ATPV 21cal/cm²
- 100% Cotton, 14oz Arc Denim
- Flame retardant corespun 40 thread
- YKK concealed brass zip
- Double needle top stitching at inleg & back rise
- Swing pockets with double needle topstitch
- Five belt loops
- Back yoke with double needle topstitching
- Two back pockets with double needle topstitching
- cal/cm² Rating embroidery on right back pocket

Sizes: 28 - 50

- Substations & switchrooms
- Utilities & power generators
- Industrial electrical maintenance & installations
- Mining, chemical & refineries







15CAL ARC DUST COAT

CODE: DW-ARCDC













NFPA 2112, NFPA 70E, ASTM F1959, ASTM F2621-12, EN 11611:2015, EN 11612:2015, EN 61482-1-2:2014, EN ISO 204471:2013, SANS 724

- ATPV 15cal/cm²
- Dromex A.P.T Fabric 88% Cotton, 12% Nylon, 305gsm
- Flame retardant thread throughout
- Concealed flame retardant plastic snap buttons & 25mm x 85mm hook & loop closure at front
- Flame retardant rib cuff
- 50mm Lime/silver/lime flame retardant reflective tape on arms, chest and "X" on back
- Triple needle topstitched shoulders & armholes
- Slit at centre back hem
- cal/cm² Rating embroidery on right breast

Sizes: S-5XL

- Substations & switchrooms
- Utilities & power generators
- Industrial electrical maintenance & installations
- Mining, chemical & refineries







9.9CAL T-SHIRT UNDERGARMENTS

CODE: DW-ARC9.9-LST (LONG SLEEVE) **DW-ARC9.9-SST (SHORT SLEEVE)**









EN OEKO-TEX®

IEC 61482-1-2, NFPA 2112, NFPA 70E, ASTM F1959, EN 11611:2015, EN 11612:2015, EN 61482-1-2:2014

- ATPV 9.9 cal/cm²
- 88% Cotton, 12% Nylon Interlock FR Knitted Fabric, 203gsm
- Flame retardant thread throughout
- Flame retardant knitted rib cuffing
- cal/cm² Rating embroidery on left breast
- Suitably worn under any Dromex Arc garment

Sizes: S - 5XL

- · Substations & switchrooms
- Utilities & power generators
- · Industrial electrical maintenance & installations
- · Mining, chemical & refineries





9.9CAL BOXER SHORTS

CODE: DW-ARC 9.9-BSH









IEC 61482-1-2, NFPA 2112, NFPA 70E, ASTM F1959, EN 11611:2015, EN 11612:2015, EN 61482-1-2:2014

- ATPV 9.9 cal/cm²
- 88% Cotton, 12% Nylon Interlock FR Knitted Fabric, 203gsm
- · Flame retardant thread throughout
- · Flame retardant knitted waist band
- cal/cm² Rating embroidery on left leg
- Suitably worn under any Dromex Arc garment

S - M Sizes: L - XL

Suitable Use:

- · Substations & switchrooms
- · Utilities & power generators
- · Industrial electrical maintenance & installations
- · Mining, chemical & refineries



FLAME RETARDANT SOCKS

CODE: DF-9162-CH-L

- Ribbed cuff for secure fit
- Reinforced heel & toe for durability
- Blister resistant
- Thermally balanced & odour free
- Will not burn when exposed to heat & flame 80% Wool, 15% Nylon, 4% Lycra, 1% Elastane Aflammit® ZR treated yarn

Sizes: Large (8 - 11)

- Petroleum service industry
- Petrochemical industry
- Oil & gas industry
- Electrical & gas utility
- Steel mills
- Fighter pilots

NEW



ARC BALACLAVA







NFPA 70E & NFPA 2112

- 100% Meta-Aramid
- Single layer: 203gsm fabric Double layer: 406gsm fabric
- Flame retardant thread throughout
- Lightweight & breathable

Suitable Use:

Fire caused by -

- Chemicals
- Petrochemicals
- Utility/Electrical work

Sizes: One size fits all





31CAL ARC BEANIE

CODE: DW-ARC-BEAN











NFPA 70E & NFPA 2112

- ATPV 31 cal/cm²
- 88% Cotton, 12% Nylon Interlock FR Knitted Fabric, 406gsm
- Double layer construction for insulation
- Pleated crown area for snug fit
- Lightweight & breathable

Suitable Use:

- Mining
- Petrochemicals
- **Utilities & Power Generation Substations & Switchrooms**

Sizes: One size fits all

55CAL ARC BLANKET

CODE: DW-ARCBLANK











NFPA 70E & NFPA 2112

- Dromex A.P.T Fabric 88% Cotton, 12% FR Nylon
- Two-layer panel system
 - > 14 oz Layer 1
 - > 14 oz Layer 2
- · Inherent FR thread throughout
- Heat transfer print & FR APTV 55cal embroidery
- Ten double-layer loops for securing in place
- Centralised cable strap with Velcro/zip strap
- Provides protection against arc blast hazards during electrical work in confined spaces



Suitable Use:

- Substations & switchrooms
- Utilities & power generators
- Industrial electrical maintenance & installations
- Mining

Sizes:

• Small: 1.5m x 2.4m • XLarge: 2.5m x 4m







ERGOS INTEC ARC HELMET

CODE: ARC ERGOS 28

- ATPV 28 cal/cm²
- Insulated helmet with integrated retractable visor & chin protection
- Provides safety against thermal hazards of an electric arc & projected droplets of molten metal
- Electrical insulation 1000V AC & 1500V DC
- Conforms to EN 166:2001, EN 170:2002, EN 50365:2002, EN 397:2012 + A1:2012, GS-ET-29:2011 & ASTM F2178-17b
- Suitable for use by electricians during work on live equipment and work at heights on electrical connections





ERGOS2 ARC VISOR

CODE: ARC ERGOS2 12 / 12-EU / 27

- Increased worker safety because of REAL VIEW of work environment.
- New generation of face protection against the thermal hazards and impact of an arc flash
- Tested to EN 166 for protection against molten metals & hot solids
- Realistic colour reproduction >95%
- Protection against high-speed particles: medium energy impact (B)
- · Extended length visor & transprent chin guard
- Optimised weight balance & no time limit on durability
- Fitted with a universal bracket for use with front brim arc rated hard hats according to EN 50365 or EN 397 standards
- Available in 12 cal/cm² & 27 cal/cm²

AVAILABLE IN EURO HELMET SLOT MOUNTED OPTIONS: 12 cal/cm² & 26 cal/cm²





ARC HARD HAT

CODE: ARC HHSG 18

- Electric hard hat offering dielectric protection up to 20 000 volts
- 4-point quick fit suspension
- Adjustable Fast-Trac III rachet
- Fixed stitched sweat band
- · Easily integrated with face and hearing PPE
 - Suitable for use in electric / utilities & manufacturing industries



70CAL ARC SWITCHING GLOVES

CODE: DG-ARC70









OEKO-TEX®

NFPA 2112, NFPA 70E, ASTM F2675, IEC 61482-1-1, IEC 61482-1-2, EN 11611, EN 11612, EN 61482

- ATPV 70cal/cm²
- Dromex A.P.T Fabric 88% Cotton, 12% Nylon
- · Flame retardant glove lined with meta aramid mat lining
- · Inherent FR stitching throughout
- Glove thickness: 2.7mm
- Elasticated shirred glove for comfort

Sizes: S/M & L/XL

Suitable Uses:

- Substations & switchrooms
- Utilities & power generators
- Industrial electrical maintenance & installations



100CAL ARC SWITCHING GLOVES

CODE: DG-ARC100











OEKO-TEX®

NFPA 2112, NFPA 70E, ASTM F2675, IEC 61482-1-1, IEC 61482-1-2, EN 11611, EN 11612, EN61482, SANS 724

- APTV 100cal/cm² mitt-style glove
- Dromex A.P.T Fabric 88% Cotton, 12% Nylon
- Triple layer construction: 14oz outer, 700gsm meta aramid mat lining & 14oz inner
- Inherent FR stitching throughout
- Elasticated shirred glove for an ideal fit
- cal/cm² Rating embroidery on cuff

Sizes: S/M & L/XL

- Substations & switchrooms
- Utilities & power generators
- Industrial electrical maintenance & installations







16.8CAL ARC FLASH DIPPED GLOVE

CODE: NE423AF

EN 388







ASTM

F2675/F2675M-13 D 3776:2013 Option C

- 42.3cal/cm² Arc rated palm & 16.8cal/cm² arc rated back
- Excellent grip in wet, oily & dry environments
- · High dexterity
- · High resistance to snatch, tear, cut, abrasion & heat
- · Basic chemical oil stability
- Seamless knitted aramid fibre glove with a textured
 Nitrile micro foam & neoprene coated palm
- 13g Aramid flexibile knit fabric
- Extended 16cm cuff

Sizes: 7 - 13

Suitable Use:

- · Power & utility companies
- Installation, maintenance & repairs

51CAL LEATHER ARC GLOVE

CODE: CA420



3X33D







ASTM

F2675/F2675M-13

- 51cal/cm² Arc rated leather gloves
- High cut level D protection
- High abrasion resistance
- High resistance to snatch, tear, cut & heat
- Multi-layer protection provides flexibility, comfort & excellent insulation
- Leather glove lined with Aramid fibre
- Kevlar stitching
- · Shirred extended 16cm cuff
- Cow split leather 1mm

Sizes: 8 - 11


- Power & utility companies
- Installation, maintenance & repairs of high voltage equipment





ARC FLASH TREAD SAFETY BOOT

CODE: DF-FLASH



















- Conforms to EN ISO 20345:2011
- Waterproof full grain cow leather upper
- Slip resistant outsole, SRC (Slip resistance on ceramic tile floor with NaLS & on steel floor with glycerine^c)
- Kevlar midsole protects from penetrating objects & heat
- Energy absorbing heel
- Removabe insole
- Oil resistant
- Contact heat resistant outsole at 300°C for 60 seconds
- Composite toe cap is impact resistant up to $200 \pm 4J$
- Cleated outsole for additional traction
- Dual velcro closure strap design for ease of use with gloves

Sizes: 3 - 13

- Arc flash & flash fire potential
- Manufacturing (incl. computer equipment)
- Refineries





INNOVATION

POSEIDON 220 FR PROTECTION BY DROMEX

Poseidon 220: Flame Retardant Overalls

Introducing our new oil & gas overalls designed and developed to meet the exacting needs and tough challenges faced by our customers and end users working within this demanding and highly specialised sector, globally.

We know how one step closer can feel too close, how it feels to face danger every day. That's why our premium Poseidon boilersuit is HRC 2 Arc Rated, anti-static, features an action back for enhanced comfort and has adjustable sleeves & legs for a secure fit and extra pockets.

This lightweight workwear includes EN approved reflective tape around the legs, arms and over the shoulders for greater visibility.

Made with our unique Dromex F.P.TTM flame retardant fabric blend, which has been engineerd to provide superior protection against heat, fire, oil and gas hazards and is proudly locally manufactured at our state-of-the-art workwear facility, Dromex Globale, situtated in KZN, South Africa.

Tested to leading international NFPA, ASTM, EN & IEC standards: IEC 61482-1-1, IEC 61482-1-2, NFPA 2112, ASTM F1959, ASTM F2621-12, EN 11611, EN 11612 & EN 61482.

Encompassing both European ISO/EN norms and US NFPA standards, our new Poseidon 220 range maximises stock control, enabling suppliers and distributors to participate in all major PPE regions around the world.

Therefore, Poseidon 220 fabrics offer much greater value and flexibility in diverse market conditions.

In addition to achieving these European and US technical standards, Poseidon 220 fabrics have also come with Oeke-Tex Class II level for formaldehyde requirements, distinguishing this new range as a complete and total package of Flame Retardant Fabrics, with global market application.

Innovatively developed to deliver optimum protection, the Poseidon 220 range offers the ultimate combination of superb technical and aesthetic product quality and certified standards supported with versatile delivery options and excellent customer service.

POSEIDON 220

98% Cotton, 2% Anti-static

220 gr/m²

Certified to: EN 11611, EN 11612, EN 1149, EN 61482, ASTM. NFPA

Dual certified to NPFA / EN norms

Low formaldehyde: Class II - below 73 ppm formaldehyde Global market application

Giobai market application

Maximized stock control: no need to have different certified fabrics for different markets, offering more flexibility.

We believe that all employes are entitled to maximum protection without compromise. From essential PPE to our specialised FIRE protection, it is our responsibility to supply products that will deliver on this promise and it's not something we take lightly.















POSEIDON OIL & GAS BOILERSUIT

CODE: DW-POS220RT





















IEC 61482-1-1, IEC 61482-1-2, NFPA 2112, ASTM F1959 ASTM F2621-12, EN 11611, EN 11612, EN 61482

- Dromex F.P.TTM Fabric 98% Cotton, 2% Anti-static, 220gsm
- ATPV 8 cal/cm²
- Inherent flame retardant thread
- Action back design with pleats for extra comfort & freedom of movement
- Flame retardant hook & loop strip above right chest pocket for attachment of a name badge
- Concealed nylon zip with branded puller & nylon press stud
- 50mm Silver FR reflective EN approved tape on shoulders, arms & legs
- Triple needle topstitched garment
- Mitred breast & back pockets with flaps & concealed FR hook & loop closure
- Left shoulder tape has a gas detector/radio loop with concealed FR hook & loop
- A pen pocket on left sleeve
- Waist side swing pockets with inner side opening
- Side tool pocket
- Adjustable sleeve cuff & leg hem with nylon press stud

Sizes: 32 - 64

- Oil & gas
- Refineries









DuPont™ Nomex_® **FIRE BOILERSUIT**

CODE: DW-NOMEX-O













Conforms to SANS 434 NFPA 70E, NFPA 1975, NFPA 2112, EN1149-3 ANTI-STATIC, EN 1149-1, EN 13034 ASTM F1506, ASTM D6413 Flame resistance of textiles

- DuPontTM Nomex, 203gsm Fabric
- Inherent flame retardant yarn
- Two-way NOMEX YKK concealed brass zip
- 50mm Silver flame retardant double needle topstitched reflective tape on arms & legs
- Fully triple needle topstitched garment
- Two-way radio pocket with 25mm Velcro, mitred breast pocket with velcro V-flap & gas analyser tab, side pockets, two mitred back pockets with Velcro monza flap

32 - 64 Sizes:

- Petroleum
- Petrochemical
- Chemical
- Fire fighters







DuPont™ Nomex.

FIRE SUIT

CODE: DW-NOMEX-J / P













Conforms to SANS 434 NFPA 70E, NFPA 1975, NFPA 2112, EN1149-3 ANTI-STATIC, EN 1149-1, EN 13034 ASTM F1506, ASTM D6413 Flame resistance of textiles

- DuPontTM Nomex, 203gsm Fabric
- Inherent flame retardant yarn
- NOMEX YKK concealed brass zips on jackets & pants
- Triple needle topstitched garment
- 50mm Silver flame retardant reflective tape on arms & legs for increased visibility
- Mitred laid on jacket pockets, mitred breast pocket with Velcro closure, side slits, hip pocket & mitred cargo pocket both with Velcro flap on pants & one back pocket

Sizes:

- Jackets: 32 60
- Pants: 28 56

- Petroleum
- Petrochemical
- Chemical
- Fire fighters





WILDLAND GOGGLES

CODE: DV-EF20B











- Fire resistant polycarbonate lens
- Fire proof adjustable headband
- Red fire retardant PVC eye frame
- Designed for compatibility with other PPE
- Easy to put on with gloves
- Lightweight, non-vented goggles
- Anti-Scratch
- Anti-fog lens
- Contoured to ensure a firm fit
- Provides protection from flying debris

- Complies to ASTM F2894 for heat resistance up to 260° C, $6/-0^{\circ}$ C (8,4,6)
- NFPA 1977:2016
- ANZI Z87 NFPA 1971 & 1977

Suitable Use:

- Fire marshall
- **Bush fires**
- Work around active helicopters
- Extrication
- Working with chain saws / hoses
- Emergency / first responder operations
- Chemical splash



BALACLAVA

CODE: DW-BALAS / D







NFPA 70E & NFPA 2112

DW-BALAS: Single Layer DW-BALAD: Double Layer

- Inherent knitted fabric
- 100% Meta-Aramid
- 190gsm fabric
- Flame retardant thread throughout
- Lightweight & breathable

Suitable Use:

Fire caused by -

- Chemicals
- Petrochemicals 190gsm fabric
- Utility/electrical work

Sizes: One size fits all





FIRE & CHEMICAL BOOTS

CODE: DFB

























EN 15090:2012 approved

- Lightweight firefighting boots
- Suitable against chemicals & can be worn with chemical encapsulated suits
- Has the highest chemical protection, Type 3
 (fire suppression, rescue interventions including protection against chemical hazards)
- Reflective strips & trim can be seen as far as 250m away
- Rot proof inner lining

Suitable Use:

- Structural & wildland fire fighting applications
- Search & Rescue
- Aircraft fires
- Petrochemical fires

- Made of Elastomer: fireproofed NBR/CR (fireproofed nitrile/polychloroprene rubber)
- EN 15090 approved firefighting boots and Marine Fire Protection certified, used in many European countries
- 10 Year shelf life
- Composite polymer toe cap & midsole for impact & puncture protection (ladies sizes 3 & 4 ½ has a steel toe cap)
- Weight (size 8): 1900g per pair

Sizes: 3 - 11 ½ *Ladies size options available

SIZING GUIDE

EUR	36	37/38	39	40/41	42	43	44	45	46/47
UK	3	4 ½	5 ½	7	8	9	9 ½	10 ½	11 ½









CODE: DW-HYB-RB







- 80/20 Poly Cotton, 200gsm fabric
- Concealed DRO aluminium zip on jackets & pants
- Triple needle topstitched inleg & back rise
- Polyester for colour-fastness blended with cotton for comfort & breathability
- Left breast pocket
- · Side entry pants pockets

HYBRID-RT:

- 50mm Lime/silver/lime reflective webbing tape on arms & legs
- Sold as a set



HYBRID SUIT REFLECTIVE

CODE: DW-HYBRT-RB







Sizes: 32 - 50

- Construction
- Landscaping
- · General purpose
- Maintenance







CONTI SUIT RT

CODE: DW-CONTI-RT



















DW-CONTI-RT:

 50mm Lime/silver/lime reflective webbing tape on arms & legs

Sizes: 30 - 64

Suitable Use:

- Warehouses Workshops
- Gardening
 Construction
- Janitorial General purpose

CONTI SUIT

CODE: DW-CONTI















GY WHT

- 80/20 Poly Cotton, 200gsm fabric
- Concealed DRO aluminium zip on jackets & pants
- Overlocked stitching on shoulders and armholes
- Triple needle topstitched inleg & back rise
- Left breast pocket with pen division & V-flap with concealed press stud
- Side entry pants pockets
- · Right back pocket
- · Reinforced bar-tacks
- Polyester for colour-fastness blended with cotton for comfort & breathability
- · Sold as a set





MAXIMUS CONTI SUIT

CODE: DW-MAXIMUS





- 80/20 Poly Cotton, 200gsm fabric
- Concealed DRO zip closures
- Triple needle topstitched jacket shoulders, armholes and side seams
- 2 Open laid on waist pockets, 1 open left chest pocket with a pen pocket and 1 right breast pocket with a V-flap and a concealed metal press stud closure.
- Two front pants swing pockets and an open mitred back pocket with
- All pant seams are triple stitched for added durability
- Inner elasticated waist for optimum fit and flexibility with 7 belt loops
- Ruler/tool pocket on rear right leg
- Generous cut made with Polyester & Cotton blend for colour-fastness, comfort & breathability.
- Sold as a set

Sizes: 30 - 60

Suitable Use:

- · Logistics
- Warehousing
- Construction
- Workshops, maintenance & repairs
- Gardening & general-purpose applications

RB

NB

RD

EG

BACK IN STOCK



80/20 DUST COAT

CODE: DW-8020XX-DC





- 80/20 Poly Cotton, 200gsm fabric
- Concealed metal press stud closures
- Triple needle topstitched shoulders and armholes
- Left breast mitred pocket & V-flap with concealed press stud
- 2 mitred waist pockets
- · Slit at back centre back hem
- Polyester blended with Cotton for colour-fastness, comfort & breathability.

Sizes: XS - 3XL

- Laboratories
- · Hospitals
- Warehousing
- · General supervision in industries













HACCP DUST COAT

CODE: DW-HACCP-XX-DC





- 65/35 Poly Cotton, 235gsm fabric
- Double concealed press stud closures
- Triple stitched shoulders, armholes and side seams
- Left breast internal pocket
- Back slit on rear of coat for flexibility and ease of movement
- · Partially elasticated sleeve cuffs
- Polyester blended with Cotton for colour-fastness, comfort & breathability.

Sizes: XS-3XL

Suitable Use:

Food Industry

WHT

RB

NB

RD



HACCP JACKET & PANTS

CODE: DW-HACCP-XX-J / P





- 65/35 Poly Cotton, 235gsm fabric
- Pull over jacket with a V-neck chest and collar
- Triple stitched jacket shoulders, armholes and side seams
- Left breast internal pocket
- · Partially elasticated jacket sleeve cuffs
- · Triple stitched, elasticated pants with drawstring
- · Pants back pocket with flap closure
- Polyester blended with Cotton for colour-fastness, comfort & breathability.

Sizes:

Jackets: 30 - 60Pants: 26 - 56

Suitable Use:

Food Industry



RB



RD







65/35 TWO-TONE JACKET

CODE: DW-6535XX-2TJ







- 65/35 Poly Cotton, 235gsm fabric
- · Concealed DRO aluminium zip
- Triple needle topstitched garment
- 2 Mitred breast pockets with V-flaps & concealed press stud closure, left breast pocket with pen division
- 2 Open mitred waist pockets
- Polyester blended with Cotton for colour-fastness, comfort & breathability.

Sizes: XS - 5XL

- · Farming & Agriculture
- Warehouses
- Workshops
- Construction
- General purpose
- Maintanance & repairs







65/35 SANS 434 FIT JACKET & PANTS

CODE: DW-6535XX-J/P







- 65/35 Poly Cotton, 235gsm fabric
- · Concealed DRO aluminium zip on jackets & pants
- Triple needle topstitched garment
- 2 Mitred breast pockets with V-flaps & concealed press stud closure, left breast pocket with pen division
- 2 Open mitred waist pockets
- 2 Side swing pockets and 2 rear mitred open pocket on pants
- · Side tool pocket
- Polyester blended with Cotton for colour-fastness, comfort & breathability.
- Jackets & pants sold separately

Sizes:

Jackets: 30 - 60Pants: 26 - 56

- Logistics
- Warehouses
- Workshops
- Gardening
- Construction
- General purpose
- Maintanance & repairs









BETHE ONE WHO GETS IT DONE.

OUR NEW TECHNICAL UTILITY RANGE IS IN STOCK NOW!

The new versatile and multifunctional Dromex Technical Utility range has been engineered to perform so you can be the one who gets it done.

Some premium features include:

- Multifunctional custom pockets (ruler/pen pocket, mobile phone pocket and cargo pocket).
- Reflective piping on rear leg pockets, rear ankle and knee area for added visibility in dark environments.
- Hammer/tool loop.
- Seams are triple needle topstitched for added durability.
- Stress areas are bar tacked.
- Inner elasticated waist for optimum fit and flexibility with 7 belt loops.
- Reinforced canvas panels and a comfortable spacious crouch area for ease of movement.
- Available in 2 contrasting colours, Sand and Carbon.

We're committed to supplying quality without compromise and this promise is at the forefront of every piece of Dromex Workwear.







UTILITY PANTS & SHORTS

CODE: DW-UTI-PN (PANTS)
DW-UTI-SH (SHORTS)

- 65/35 Poly Cotton & 300D water-resistant 100% Polyester Oxford, 280gsm
- · Concealed nylon zip
- Triple needle topstitched garment
- Multifunctional custom pockets (ruler/penpocket, mobile phone pocket & cargo pocket)
- Reflective piping on rear ankle, knee area and back pockets
- Hammer/tool loop
- · Concealed elasticated waistband
- Reinforced canvas panels for added durability



 Polyester blended with Cotton for colour-fastness, comfort & breathability

Sizes: 28 - 50

- · General purpose
- Maintenance & repairs
- Workshops
- Logistics
- Rigging





UTILITY JACKETS

CODE: DW-UTI-J

- 65/35 Poly Cotton & 300D water-resistant 100% Polyester Oxford, 280gsm
- Multifunctional custom pockets 2 waist pockets with zip closure
- 2 chest pockets with hook and loop closure:
 - left pocket has multiple pens pocket
 - right pocket with a concealed side entry pocket
 & zip fastener, an inner mobile phone pocket with hook and loop fastening
- · A pen/ruler pocket on the left arm
- · Adjustable sleeve cuffs
- Adjustable waist band with press stud fasteners.
- Action back pleats at rear of jacket for comfort and flexibility
- · Reflective piping for enhanced visibility
- Stress points are bar tacked

Sizes: S - 3XL

Suitable Use:

- General purpose
- Maintenance & repairs
- Workshops
- Logistics
- Rigging

KH

CA

COMING SOON





FLAME ACID TECHNICAL UTILITY JACKET & PANTS

CODE: DW-UTI-PN/J-AB

EN 6530:2005 EN 14116:2015







- 100% Cotton fabric, 280gsm
- A flame retardant & coated acid resistant fabric
- Multifunctional custom pockets 2 waist pockets with zip closure
- 2 chest pockets with hook and loop closure:
 - left pocket has multiple pens pocket
 - right pocket with a concealed side entry pocket
 & zip fastener, an inner mobile phone pocket
 with hook and loop fastening
- A pen/ruler pocket on the left arm
- · Adjustable sleeve cuffs
- Adjustable waist band with press stud fasteners.
- Action back pleats at rear of jacket for comfort and flexibility
- · Reflective piping for enhanced visibility
- · Stress points are bar tacked
- · Jackets & pants sold separately

Sizes:

Jackets: S - 5XLPants: 28 - 50

- Engineering
- Construction
- Welding
- Maintanance & repairs







KNEE PAD TECHNICAL UTILITY PANTS

CODE: DW-UTI-KPN-BLK

- 65/35 Poly Cotton & 300D water-resistant 100% Polyester Oxford, 280gsm
- Top loading pre-shaped knee pad pockets for use with Dromex knee pads (DW-UTI-KPAD)
- · Concealed nylon zip
- · Triple needle topstitched garment
- 10 Multifunctional custom pockets (tool pockets, ruler/ pen-pocket, mobile phone pocket & cargo pocket)
- Reflective piping on knee, back pockets and cargo pockets
- · Hammer/tool loop
- · Concealed elasticated and rubberised waistband
- Reinforced canvas panels for added durability
- Polyester blended with Cotton for colour-fastness, comfort & breathability

Sizes: 28 - 50

Suitable Use:

- General purpose
- Maintenance & repairs
- Workshops
- Logistics
- Rigging

TECHNICAL UTILITY KNEE PADS

CODE: DW-UTI-KPN-BLK

- Ergonomically designed to adapt to the shape of the knees while bending
- Shock absorbent
- · Lightweight, soft & durable
- · Can be cut to size as required
- Sold separately

Sizes: One size



QUICK DRY T-SHIRTS

CODE: DW-TECH-T



- 100% Polyester, 140gsm fabric
- Premium crew neck t-shirt
- Lightweight polyester moisture management fabric for added comfort
- · Quick drying garment
- The natural fibres & relaxed fit design makes this garment comfortable & breathable
- Available in five colours

Sizes: XS - 5XL

Suitable Use:

- Corporate wear
- Promotional wear
- Active wear
- General work environments
- Warehouses







RB

RD







POLY VISCOSE ACID JACKET & PANTS RT

CODE: DW-PVACID-RT







SANS 434 & ISO 6530

Protection from the following chemicals: HCl, H₂SO₄, N9OH, Caustic Soda

- 80/20 Poly Viscose, 270gsm fabric
- YKK Concealed brass zip on jackets & pants
- · Full triple needle topstitched garment
- Mitred left breast pocket & jacket pockets
- Side entry pants pockets & rear right pocket
- 50mm Lime/silver/lime reflective webbing tape on arms, chest, legs & an "X" on the back
- A coated acid resistant fabric that prevents wetting by acids or moisture
- · Protection in the event of accidental chemical spillage
- Jackets & pants sold separately

Sizes:

• Jackets: 32 - 64

Pants: 28 - 60

- Chemical industry
- · Cleaning industry
- · Brewing industry
- · Mining industry



ACID RESISTANT CONTI SUIT

CODE: DW-ACID









Protection from the following chemicals: **HNO3, HCI, H2SO4 & NaOH**

- 80/20 Poly Cotton, 200gsm fabric
- YKK concealed metal zip on jackets and pants
- Triple topstitched shoulders, armholes, in-leg & back rise
- Left breast pocket with pen division & V-flap
- Side entry pants pockets & rear right pocket
- A coated acid resistant fabric that doesn't allow wetting by acids or moisture
- Protection in the event of accidental chemical spillage
- · Sold as a set

Sizes: 30 - 60

- Chemical industry
- Cleaning industry
- Brewing industry







REFLECTIVE SHIRTS

CODE: DW-HVSS / LS



- 100% Cotton, 135gsm fabric
- Reflective operational shirt
- Vented back yoke for comfort in heat
- 50mm Silver reflective tape on sleeves, around the chest & waist
- Mitred pockets have double needle topstitching
- **Button closure**
- The natural fibres make this garment comfortable & breathable
- Ideal with navy J54 Cargo Pants or Dromex Denims

NOTE:

- Two-tone shirts orange/navy & yellow/navy available in short sleeve & long sleeve
- Navy available in long sleeve only

Sizes: S-5XL

Suitable Use:

- Construction
- **Outdoor** inspections
- Outdoor work in hot climates
- Mining







J54-RT CARGO PANTS SABS SPEC

CODE: DW-CARGO-PRT







- 100% Cotton, 220gsm fabric
- YKK concealed brass zip
- Fully triple stitched trousers
- Mitred cargo pockets with mitred flap & hook & loop closure
- Right cargo pocket includes cell phone division
- 50mm Silver reflective tape on legs
- The natural fibres make this garment comfortable and breathable

Sizes: 26 - 50

- Construction
- Logistics
- General purpose



DENIM JACKET & PANTS SANS 434 FIT

CODE: DW-DENIM-J / P



- 100% Cotton indigo blue denim, 12oz fabric
- YKK Concealed brass zip on jackets & pants
- Full triple needle topstitched jacket & pants
- Rounded left breast pocket and two front jacket pockets with mitred flaps
- Bar-tacks on all stress points
- Rounded back pocket & side entry pants pockets
- Tool pocket on the back right leg
- The natural fibres make this garment comfortable & breathable
- Jackets & pants sold separately

Sizes:

Jackets: 30 - 64Pants: 26 - 60

- Construction
- Engineering
- Steel foundry
- Automotive







J54 100% COTTON JACKET & PANTS

CODE: DW-J54XX







- 100% Cotton, 220gsm fabric
- Concealed DRO aluminium zip on jackets & pants
- · Triple needle topstitched garment
- Double needle topstitched yokes
- Mitred left breast pocket with V-flap & two open mitred waist pockets
- Swing pockets on pants & rear right pocket
- The natural fibres make this garment comfortable & breathable
- Jackets & pants sold separately

Sizes:

Jackets: 32 - 64Pants: 26 - 60

- Agriculture
- Construction
- Logistics
- General work environments















J54 RT MINING SPEC BOILERSUIT

CODE: DW-J54-ANGXX / UB



Compliant to SANS 434 & SANS 1387-4

- 100% Cotton, 220gsm fabric
- 6 Pocket artisan boilersuit
- 50mm Lime/silver/lime reflective tape with double needle topstitching around arms, legs, strips above breast pocket & "X" on the back
- · Concealed NG5 metal button closure
- Full triple needle topstitched garment
- 2 x Mitred breast pockets with monza NG5 metal button flaps
- · Concealed elasticated waistband
- Side swing pockets & slits
- Mitred back pocket
- Side tool pocket on right leg
- The natural fibres make this garment comfortable & breathable

Sizes:

Royal blue: 30 - 64Other colours: 30 - 66

Suitable Use:

- Mining
- Agriculture
- Construction
- Logistics



OR

RB

RD







J54 RT MINING SPEC JACKET & PANTS

CODE: DW-J54-ANGXX







Compliant to SANS 434 & SANS 1387-4

- 100% Cotton, 220gsm fabric
- · YKK Concealed brass zip on jackets & pants
- 50mm Lime/silver/lime reflective tape around arms, legs, strips above breast pocket & "X" on the back
- Full triple needle topstitched garment
- Mitred left breast pocket with press stud closure & mitred flap
- Two open mitred waist pockets
- Ruler pocket
- The natural fibres make this garment comfortable & breathable
- · Jackets & pants sold separately

Sizes:

Jackets: 32 - 64Pants: 28 - 60

- Mining
- Agriculture
- Construction
- Logistics
- Engineering











D59 RT MINING SPEC BOILERSUIT

CODE: DW-D59-ANGUB-B







Compliant to SANS 434 & SANS 1387-4

- Premium Mining Garment
- 100% Cotton, 270gsm D59 unbleached
- Double thickness patches on elbows, seat & knees for enhanced durability
- 50mm Lime/silver/lime reflective tape with double needle topstitching around arms, legs, strips above breast pocket & "X" on the back
- · Concealed metal button closures
- · Full triple stitched garment
- 2 x Mitred breast pockets with monza NG5 metal button flaps
- · Concealed elasticated waistband
- · Side swing pockets & slits
- Mitred back right pocket
- Side tool pocket on right leg
- The natural fibres make this garment comfortable & breathable

Sizes: 30 - 64

- Mining
- Construction







D59 MINING BOILERSUIT

CODE: DW-D59MXX









Compliant to SANS 434 & SANS 1387-4

- 100% Cotton, 270gsm Fabric
- Two-way YKK concealed brass zip
- Full triple needle topstitched garment
- 50mm Silver reflective tape over shoulders, around arms, around legs & 50mm flame retardant orange reflective tape on back
- Left breast pocket with V-flap, concealed press stud closure & pen division on top of flap.
- Cargo pocket with concealed press stud V-flap & patch back hip pocket
- The natural fibres make this garment comfortable
 & breathable
- Reflective "Sasol" logo on left breast pocket

Sizes:

• White: 32 - 64

• Yellow & Orange: 30 - 64

Suitable Use:

Mining

Steel installations

Rigging

YL

OR

WHT



D59 FLAME RT JACKET & PANTS

CODE: DW-FLAMERT-J/P









Compliant to SANS 1387-4, SANS 1423-1 & SANS 434

- 100% Cotton, 320gsm fabric
- YKK Concealed brass zip on jackets & pants
- Triple needle topstitched garment
- · Left breast pocket with concealed press stud
- Two open mitred waist pockets
- Front swing pants pockets
- · Rear mitred right pocket
- 50mm Lime/silver/lime reflective webbing tape on arms, legs, chest & back
- The natural fibres make this garment comfortable & breathable
- · A flame retardant finish coated fabric
- · Reflective tape for visibility
- · Jackets & pants sold separately

Sizes:

Jackets: 30 - 64Pants: 26 - 60

- Construction
- Welding
- Boiler shops
- Foundry
- · Heavy engineering







D59 RT JACKET & PANTS

CODE: DW-D59RT-J / P









Compliant to SANS 434 & SANS 1387-4

- 100% Cotton, 270gsm fabric
- YKK Concealed brass zip on jackets & pants
- 50mm Lime/silver/lime reflective tape around arms & legs with double needle topstitching
- Full triple needle topstitched garment
- Mitred left breast pocket with press stud closure & mitred flap
- Two open mitred waist pockets
- · Front swing pants pockets
- Rear mitred right pocket
- · Ruler pocket on right leg
- The natural fibres make this garment comfortable & breathable
- Jackets & pants sold separately

Sizes:

Jackets: 32 - 62 Pants: 28 - 58

- Mining
- Agriculture
- Construction
- · Engineering
- Steel installations
- Rigging





D59 FLAME & ACID JACKET & PANTS

CODE: DW-D59FA-J / P











SANS 434, SANS 1387-4, SANS 1423-1, ISO 6530 (HNO₃, HCI, H₂SO₄ & NaOH)

- 100% Cotton, 320gsm fabric
- A flame retardant & coated acid resistant fabric
- 50mm Silver flame retardant double needle topstitched reflective tape on arms & legs
- YKK Concealed brass zip on jackets & pants
- Mitred laid on jacket pockets, mitred breast pocket with flap, mitred hip pocket & tool pocket on pants
- · Double needle topstitched mitred back pocket
- · Full triple needle topstitched garment
- Elasticated cuffs & side slits on jacket
- The natural fibres add comfort & breathability
- Protection in the event of a flash fire, and accidental chemical spillage
- Jackets & pants sold separately

Sizes:

Jackets: 28 - 68Pants: 24 - 64

- Petrochemical, oil & gas
- Mining industry
- Maintenance & repairs including installations
- Utilities & power generators









D59 FLAME & ACID BOILERSUIT

CODE: DW-D59FA-O











SANS 434, SANS 1387-4, SANS 1423-1, ISO 6530 (HNO₃, HCI, H₂SO₄ & NaOH)

- 100% Cotton, 320gsm fabric
- A flame retardant & coated acid resistant fabric
- 50mm Silver flame retardant with double needle topstitched reflective tape on arms & legs
- YKK concealed brass zips with 2 way slider
- 2 Breast pockets with V-flap
- 2 Hip side pockets & side tool pocket
- 1 Back hip pocket
- Full triple needle topstitched garment
- Elasticated cuffs
- The natural fibres add comfort & breathability
- Protection in the event of a flash fire and accidental chemical spillage

Sizes: 28 - 74

- Petrochemical, oil & gas
- Mining industry
- Maintenance & repairs including installations
- Utilities & power generators



LADIES D59 FLAME & ACID JACKET & PANTS

CODE: DWL-D59FA-J / P











SANS 434, SANS 1387-4, SANS 1423-1, ISO 6530 (HNO₃, HCI, H₂SO₄ & NaOH)

- SANS 434 Ladies cut & design
- 100% Cotton, 320gsm fabric
- A flame retardant & coated acid resistant fabric
- 50mm Silver flame retardant double needle topstitched reflective tape on arms & legs
- YKK Concealed brass zip on jackets & pants
- Mitred laid on jacket pockets, mitred breast pocket with flap, mitred hip pocket & tool pocket on pants
- Side slits for comfortable fit over waist
- Double needle topstitched mitred back pocket
- Full triple needle topstitched garment
- · Elasticated cuffs
- The natural fibres add comfort & breathability
- Protection in the event of a flash fire, and accidental chemical spillage
- · Jackets & pants sold separately

Sizes:

Jackets: S - 5XLPants: S - 5XL

- · Petrochemical, oil & gas
- Mining industry
- Maintenance & repairs including installations
- · Utilities & power generators









D59 FLAME ACID SAFETY OFFICERS JACKET & PANTS

CODE: DW-D59FAOR-J / P











SANS 434, SANS 1387-4, SANS 1423-1 ISO 6530 (HNO₃, HCI, H₂SO₄ & NaOH)

- 100% Cotton, 320gsm fabric
- YKK concealed brass zip on jackets & pants
- Full triple needle topstitched garment
- 50mm Silver flame retardant reflective tape
- · Elasticated cuffs & side slits on jacket
- Mitred laid on jacket pockets & breast pocket with V-flap
- The natural fibres add comfort & breathability
- A flame retardant & coated acid resistant fabric
- · Reflective tape for increased visibility
- Protection in the event of a flash fire and accidental chemical spillage
- · Jackets & pants sold separately

Sizes:

Jackets: 30 - 60Pants: 26 - 56

- Petrochemical
- Oil & Gas
- · Mining industry
- Maintenance & repairs including installations
- Utilities & power generators



ESKOM SPEC D59 FLAME JACKET & PANTS

CODE: DW-D59ESKOM









SANS 434, SANS 1387-4, SANS 1423-1

Compliant according to the Eskom PPE Specification 240-44175132.

Manufactured in RSA with DA GAMA locally produced fabric

- 100% Cotton, 315gsm flame treated fabric
- Eskom pantone navy blue jacket & pants with "Eskom" and "Zero Harm" embroidery
- 50mm Silver retro-reflective flame retardant tape double needle topstitched on arms & legs
- Concealed heavy duty Vizlon zip & plastic press stud closure
- Mitred laid on jacket pockets, mitred left breast pocket with flap & button closure.
- Two side entry pants pockets with money pocket
 & mitred back pockets.
- Full triple needle topstitched garment
- The natural fibres add comfort & breathability
- Protection in the event of accidental flame contact
- · Jackets & pants sold separately

Sizes:

Jackets: 28 - 64Pants: 24 - 60

Suitable Use:

 Eskom Distribution, Transmission, Generation & Rotek operations in compliance with Eskom group specification









D59 FLAME ACID THERMAL JACKET

CODE: DW-D59FA-WJ





SANS 1387-4, SANS 1423-1 ISO 6530 (HNO₃, HCI, H₂SO₄ & NaOH)

- 100% Cotton
- 320gsm Flame & acid retardant fabric outer
- 100gsm Flame retardant wadding interlining
- · 220gsm Flame retardant lining
- YKK chunky nylon zip
- Double needle topstitched on shoulders & armholes
- Flame retardant 50mm silver reflective tape on arms
- · Adjustable size flap on cuff
- Two square breast pockets with press studded flaps
- Two outer square bottom pockets with press studded flaps
- Nickel press studs throughout

Sizes:

Navy blue: XS - 7XLOrange: XS - 3XL

Suitable Use:

- Petrochemical
- Oil & gas
- Mining industry
- Utilities & power generators
- Maintenance & repairs including installations

NB







WELDING JACKET

CODE: DB-WELDJ

- Flame retardant 100% Cotton jacket with premium leather sleeves
- Flame resistant Kevlar thread for durable seams
- Adjustable, stand-up, collar for neck protection
- Flame retardant reflective "X" tape on back
- Adjustable waist for enhanced torso fit
- Protects the torso & arms from welding spatter & burns
- Comfortable, breathable & lightweight

Sizes: S - 2XL

Suitable Use:

• Welding applications with exposure to intense sparks











D59 FLAME & ACID WELDERS HOOD

CODE: DW-D59FAWH-NB









SANS 434, SANS 1387-4, SANS 1423-1, ISO 6530 (HNO₃, HCI, H₂SO₄ & NaOH)

- 100% Cotton, 320gsm fabric
- A flame retardant & coated acid resistant fabric
- The natural fibres add comfort & breathability
- Protection in the event of a flash fire and accidental chemical spillage

Sizes: Standard one size (S"M)

D59 FLAME & ACID WELDERS SKULL CAP

CODE: DW-D59FASCN









SANS 434, SANS 1387-4, SANS 1423-1, ISO 6530 (HNO₃, HCI, H₂SO₄ & NaOH)

- · Engineering
- · Smelting operations
- · Mining industry
- Construction
- Oil & gas
- Petroleum
- Maintenance & repairs
- Welding industries



Protera

12.4cal PROTERA ARC **JACKET & PANTS**

CODE: DW-PROT12.4-J/P


















- ATPV 12.4 cal/cm²
- DuPont™ Protera®, 270gsm Fabric
- · Engineered flame retardant yarn
- YKK Concealed brass zips on jackets & pants
- · Adjustable Velcro closure
- · Triple needle topstitched shoulder, armhole, inleg & back rise seams
- Flame retardant Velcro closure side slits on hem of trouser
- · Nomex knitted rib cuffing
- Protera sidewinder
- Side entry pockets on jackets & pants
- 12.4 cal/cm² Rating embroidery on jacket & pants
- Jackets & pants sold separately

Sizes:

Jackets: 32 - 60 Pants: 28 - 56

Suitable Use:

Electrical arc flash












- · Retractable ventilation holes
- Ratchet type adjustment for easy fitment
- 2-Point adjustable webbed polyester chin strap
- Side slots for fitment of face & hearing PPE
- 8-Point suspension within the shell provides optimum shock absorption
- Anti-static & tested for electrical isolation at 2000 volts
- Complies with the requirements of SANS 1397:2003, Industrial Safety Helmets
- Certified to EN 397:2012+A1:2012, Industrial Safety Helmets
- MASC 20-8361 approved, Mining and Surface Certified as per 2015/021934/07
- · CE Approved



 Available with an optional lamp mounting bracket with cord holder (DH-HHCL-W) (*Cap lamp not included*)

Suitable For Use In:

- Warehousing
- General & road construction
- Surface mining
- Utilities General working at height
- Petrochemical & refineries
- Forestry





BUMP CAPS

CODE: BUMPCAP

- 80% Cotton 20% Polyester Bump Cap
- · Ventilated, baseball cap style
- Conforms to EN 812



FACE SHIELDS









HH CARRIER VISOR

CODE: DH-HHCARRIER

C E N 166

- Polycarbonate visor & ABS brow guard
- Universal face shield compatible with most industrial safety hard hats/helmets
- Provides face protection against liquid splash, medium impact particulates, molten metal & resistance to hot solids
- Suitable in construction, general industry, mining, oil & gas, utilities, airports, machining, grinding, woodwork & drilling applications

MARTCARE

CODE: DH-MARTCARE

CE

- Polycarbonate visor & brow guard carrier
- Elasticated adjustable headband
- Adjustable tilt & engage mechanism
- Provides protection against flying objects, particles, chemical splashes, splashes of molten metals & penetration of hot solids.
- Compatible for use with half mask respiratory protective devices
- Approved to EN 166

SPLASH GUARD

CODE: DH-FT2910

- A double sided, anti-fog PET Visor
- A 180° wide range isolation protection
- Transparent high definition optically correct vision
- Soft foam brow guard
- · Elasticated latex-free adjustable headband
- Compatible for use with half mask respiratory devices & spectacles
- Commonly used in medical/healthcare environments and for oil and dust exposure.
- Also suitable for use in laboratories, domestic and public places.





BREATHE EASY

CHOOSING RESPIRATORY PROTECTION

CONSIDERATIONS FOR MASK SELECTION:

- What is the oxygen content?
- Are there asphyxiants present?
- Is the atmosphere immediately dangerous to life or health?
- Is the atmosphere corrosive or likely to become so?
- Is the atmosphere explosive or likely to become so?
- Is there the possibility of permeation of air contaminants?
- What is the contaminant?
- Are there climatic extremes?

Standard	Description	Class	NPF Nominal Protection Factor	APF Assigned Protection Factor
EN 149	Filtering half mask	FFP1 FFP2 FFP3	4 12 50	4 10 20
EN 405	Valve filtering half mask	FF Gas X P1 FF Gas X FF Gas X P2 FF Gas X P3	4 50 12 33	4 10 10 10
EN 140 (Mask) EN 143 EN 14387 EN 12083	Half mask and quarter mask with filter	P1 P2 P3 Gas X Gas X P1 Gas X P2 Gas X P3	4 12 48 50 4 12 48	4 10 10 10 4 10 10
EN 136 EN 143 EN 14387 EN 12083	Full face mask (all classes)	P1 P2 P3 Gas X Gas X P1 Gas X P2 Gas X P3	5 16 1000 2000 5 16 1000	4 10 40 20 20

Particulate, Gas & Vapour Filter Selection continued on Page 87....

DISPOSABLE CUP SHAPE RESPIRATORS







QSA 2010 - FFP1 (NRCS AZ2006/21)



QSA 2020 - FFP2 (NRCS AZ2006/20)



QSA 2021 - FFP2 (VALVED) (NRCS AZ2006/29)

QSA DUST MASKS

- Suitable for a single 8-hour use against solid & water based liquid aerosols
- Protection against inhalation of dangerous particulates
- Constructed from polypropylene and polyester synthetic material preventing allergies
- Aluminium nose bridge adjuster
- Lightweight and comfortable
- Exhalation valve reduces hot air build-up & provides easy breathing in hot & humid environments (QSA 2021 only)

NRCS Homologated

- Household maintenance
- Mining
- Asbestos removal
- Agriculture
- Construction
- · General material handling



DISPOSABLE CUP SHAPE RESPIRATORS





1020 - FFP2 (NRCS AZ2004/18) Complies with BS EN 149:2001 + A1:2009 FFP2 NR D Dolomite tested as per BSI, CE 725172.



1021 - FFP2 VALVED (NRCS AZ2004/17) Complies with BS EN 149:2001 + A1:2009 FFP2 NR D Dolomite tested as per BSI, CE 725172



1231 - FFP3 VALVED (NRCS AZ2004/15) Complies with BS EN 149:2001 + A1:2009 FFP3 NR D Dolomite tested as per BSI, CE 725172



1121C VALVED - FFP2 (NRCS AZ2004/24) Complies with BS EN 149:2001 + A1:2009 FFP2 OR NR D Dolomite tested as per BSI, CE 690046



1131 VALVED - FFP3 (NRCS AZ2004/14) Complies with BS EN 149:2001 + A1:2009 FFP2 OR NR D Dolomite tested as per BSI, CE 690046

DRO-AIR 1000 SERIES

- Low breathing resistance for increased wearer comfort
- Heavy duty, tab mounted head straps (1231 only)
- Aluminium nose bridge adjuster
- Soft foam nosepiece for comfort & custom fit
- Contour face seal for performance & comfort
- Constructed from polypropylene and polyester synthetic material preventing allergies
- Exhalation valve reduces hot air build-up & provides easy breathing in hot & humid environments

ACTIVE CARBON RESPIRATORS

- Active Carbon Pre-Filter for organic vapours & welding fumes
- Low breathing resistance for increased wearer comfort
- Heavy duty, tab mounted, head straps
- An external aluminium adjustable nose clip
- Constructed from polypropylene and polyester synthetic material preventing allergies
- Soft foam nosepiece for comfort & custom fit
- Contour face seal for performance & comfort
- Exhalation valve reduces hot air build-up & provides easy breathing in hot & humid environments

N95 DISPOSABLE RESPIRATORS

 $oldsymbol{ au}$ iosh $^\circ$

- Suitable for a single 8-hour use against solid & water based liquid aerosols, that do not contain oil
- Protection against inhalation of dangerous particulates in high dust areas
- Meets CDC guidelines for M. Tuberculosis exposure control
- Can be used as part of a disease control strategy
- An ergonomic design that provides a comfortable and secure fit for different facial sizes
- A welded elastic strap along with the half face seal foam reinforces the seal with the lowest leakage.
- Lightweight with low breathing resistance for increased wearer comfort
- N95-5151 & N95-6151 includes an exhalation valve, which reduces hot air build-up & provides easy breathing in hot & humid environments
- Conforms to 42 CFR part 84, N95 class, NIOSH approved, TC-84A-448 (6151), TC-84A-7220 (5151) TC84A-7719 (5150)

- Agriculture
- Construction
- General material handling
- Medical industry applications





CODE: N95-6151



CODE: N95-5151 (VALVED)



CODE: N95-5150 (UNVALVED)



DISPOSABLE FLAT FOLD & 3 PLY RESPIRATORS





3000 SERIES

3231- FFP3 VALVED (NRCS/8072/0169) Complies with BS EN 149:2001 + A1:2009 FFP3 NR D Dolomite tested as per BSI, CE 690046

- Suitable for a single 8-hour use against solid & liquid based aerosols in high dust areas
- Low breathing resistance for increased wearer comfort
- Adjustable head straps
- Plastic adjustable nose clip
- Contour face seal for performance & comfort
- Soft foam nosepiece for a custom fit
- Exhalation valve reduces hot air build-up & provides easy breathing in hot & humid environments
- · Dolomite tested for resistance to clogging

Suitable Use:

- Mining
- Asbestos
- Agriculture
- Construction
- · General material handling industries



3 PLY MASK

CODE: DR-F103

- Suitable for a single use
- Spun bonded polypropylene non-woven fabric with filter
- Protection against incidence of cross infection of airbone infective bacterial agents - 95% filtering efficiency
- 100% Latex free ear band loop
- Hypoallergenic
- Can be used as part of a disease control strategy
- 3-Pleat triple layer construction provides stronger support
- Adjustable aluminium nose bar
- Low breathing resistance for increased comfort

- Medical
- Dental
- Food preparation
- Clean or sensitive environments

MIDI & FULL MASK RESPIRATORS





SINGLE HALF MASK

CODE: DH-101

- Soft PVC mask with deep face mould for a comfortable fit with an
 excellent seal
- Dual wide elastic headband connected with a pin swivel connector, adjustable & with a quick release toggle
- Efficient exhalation valve
- For use with the DHCS single unifit filter cartridge system



PVC TWIN HALF MASK

CODE: DH-102

- Soft PVC mask with deep face mould for a comfortable fit with an excellent seal
- Dual wide elastic headband connected with a pin swivel connector, adjustable & with a quick release toggle
- Efficient exhalation mask
- For use with the DHCT twin unifit filter cartridge system



TPR TWIN HALF MASK

CODE: DH-202

- Soft TPR (Thermo Plastic Rubber) with a deep face mould for a comfortable fit with an excellent seal
- Dual wide elastic headband with a skull cradle and a pin swivel connector, adjustable & with a quick release toggle
- Efficient exhalation valve
- For use with the DHCT twin unifit filter cartridge system



FULL FACE MASK

CODE: DH-FFM

- Premium protection against hazardous vapours, gases & particulates
- Thermo Plastic Rubber full face seal
- Anti-fog visor with 220° vision
- 5-Point comfort harness with 2 grip holes ensures easier fitting
- Lightweight dual filter cartridge system evenly distributes weight of the mask during use
- Compatible with Dromex unifit twin filters
- Designed to withstand temperatures up to 70 °C
- · One size fits all
- For use with the DHCT twin unifit filter cartridge system





BREATHE EASY

CHOOSING RESPIRATORY PROTECTION

PARTICULATE, GAS AND VAPOUR FILTER SELECTION:

Filter Type	For use against	Colour Code	Other Information
Α	Organic gases and vapours, boiling point > 65°C	Brown	EN 14387
В	Inorganic gases and vapours	Grey	EN 14387
Е	S02 and other acid gases	Yellow	EN 14387
K	Ammonia and its organic derivatives	Green	EN 14387
Hg	Mercury	Red and White	EN 14387, includes P3 particle filter Maximum use time 50 hours No class number
NO	Oxides of Nitrogen	Blue and White	EN 14387, includes P3 particle filter Single use only. No class number
AX	Organic gases and vapours, boiling point < 65°C	Brown	EN 14387 Single use only. No class number
SX	Substance as specified by the manufacturer	Violet	EN 14387
Р	Particles	White	EN 143 EN 14387
CO*	Carbon Monoxide	Black	DIN 58620 EN 14387

- Change filters as instructed by the manufacturer, e.g. 'single use only' Do not use if the expiry date on the filters has passed
- $\bullet \ \ \text{Change filters when damaged or visibly contaminated} \ \ \bullet \ \ \text{Change before the contaminant can be smelled or tasted}$
- · Change before the filter life indicated in your risk assessment
- For replaceable filters, it would be good practice to mark the filter visibly with the date it was taken out of the packaging and fitted to the RPE; an in-house replacement date can be added to this marking.

ACCESSORIES

These bags are designed to protect your reusable respiratory Midi-Mask or Full Face Mask & filters while not in use.

They also include a waist strap with quick release buckle so your equipment can be kept on you during the course of your work.



MIDI MASK BAG CODE: DHRB-BLK



FULL FACE MASK BAG CODE: DH-FFMBAG

UNIFIT FILTERS









These gas, vapour & dust filters are designed to fit the DroAir range of Midi & Full Masks. The full gas & particulate filter range is colour coded to European standards as per EN 141, EN 143 & EN 14387.

All Unifit filters are individually sealed and supplied with a replacement inhalation valve.



Single Filter Fitment
WARNING! Single filters should
only be used with single masks.



Twin Filter Fitment WARNING! Twin filters should only be used with twin masks.

SINGLE FILTERS



DHCS A1 - Organic



DHCS P2 - Particle



DHCS / DHCT P2PF Pre-filter
*Available for single & twin cartridge respirators

Suitably used with Dromex® gas cartridges that fit onto the Dromex cartridge respirators filtering out solids, dust and liquid aerosol hazards, which cannot be filtered by chemical cartridges.

 $\label{pre-filters} \mbox{ Pre-filters prolongs the life of the corresponding gas filter.}$

TWIN FILTERS



DHCT A1 - Organic



DHCT A2- Organic



DHCT B1 - Inorganic



DHCT-ABEK 1

- Organic, Inorganic, Acid & Ammonia



DHCT P2 - Particle



DHCT P3 - Particle



DHCT P3PF - Pre-filter



LISTEN UP

KNOW HEARING PROTECTION



STEPS TO SELECTION & USE The selection of hearing protection has a basic four-step method:

P

Identify:

Measure and record the potential noise hazard.



Assess:

The hazards and associated health risks should be assessed as well as other required protective equipment to ensure compatibility.



Select:

The proper hearing protection suitable for the hazard should be selected. This is made easy using the EN 352 noise reduction ratings.



Training:

Training is a very important step to optimise hearing protection by ensuring the operator is proficient in the use and limitations of his/her hearing protector.

HEARING LOSS

Hearing loss caused by exposure to noise at work continues to be a significant occupational illness despite the improvements made for comfort and attenuation. Hearing protection can play a vital part in avoiding occupational hearing loss. Although conformity to local legislation should always be a priority, cost effective solutions that are comfortable and easy to use also play a role.

Hearing loss can be gradual because of exposure to noise over time, but damage can also be caused by sudden & extremely loud noises. The damage is disabling as it can stop people being able to understand speech, keep up with conversations or it may develop into Tinnitus (ringing, whistling, buzzing or humming in the ears), a distressing condition which can lead to disturbed sleep.

EXPOSURE & PROTECTION

As a rule of thumb, if you must shout to be understood over the background noise when standing about 1 meter away from somebody, that background noise is hazardous.

Using EN352 hearing protectors, following safety requirements and testing the occupational risks assists with prevention of occupational noise-induced hearing loss.

- Protection is required if the environmental noise is over 85dB
- Noise below 75dB is considered to be non-hazardous

HEARING PROTECTION SELECTION GUIDE:











108 dB

108 dB - 24 SNR = 84 dB

84 dB

Dromex ear plugs & ear muffs are suitable for use in the following applications:

Machining & grinding, woodwork, steel cutting, aviation, high pressure steaming, shooting range, hunting, tree felling & forestry.

TYPICAL NOISE MEASUREMENTS

Stun granada

180 Rocket launching

170 Rifle shot (1m) Shotgun

160 Immediate physical damage

150 Balloon popping Aircraft engine (30m)

140 Maximum allowable exposure Riveting hammer Air raid siren

130 Immediate pain threshold Vuvuzela Punch press

120 Chainsaw

HARMFUL RANGE

115 Unprotected not allowed Nail gun Blasting Foundry rumble

Jack hammer

Machine shop
Grinding and cutting wheel

100 Pig house when feeding Sandblasting

Crushing mill

90 Industrial fire alarm

85 Hearing protection required

Hair dryer Hand saw

30 Vacuum cleaner

75 Non-hazardous

70 Inside a car

60 Normal conversation

50 Comfortable sound 40 Refrigerator

20 Whispe

20 Audible sound

Normal breathing

0 Zero





EAR PLUG DISPENSER

CODE: DRO30-DISP

CE

- Disposable ear plug dispenser that can be placed on a surface or wall-mounted
- Makes hearing protection easily accessible to staff & visitors
- Holds 500 pairs of DRO30 disposable foam ear plugs
- Refill packets sold separately (Code: DR030)

COMPOSITION:

- CE EN 352-2 (H=36 dB, M=35 dB, L=34 dB)
- SNR 37 dB

DISPOSABLE FOAM EAR PLUGS CORDED & UNCORDED

CE



CODE: DR-098C



CODE: DR-098



CODE: DR-099C

- Disposable, hi-visibility fluorescent PU foam ear plugs
- PU coated for hygiene
- Smooth, soft, pliable & easy to use
- · Superb attenuation
- Expands to fit ear canal comfortably increasing overall protection

DR-098C & DR-098 (Corded & un-corded)

- CE EN 352-2 (H=36 dB, M=34 dB, L=33 dB)
- SNR 37 dB

DR-099C (Corded)

- CE EN 352-2 (H=33 dB, M=33 dB, L=32 dB)
- SNR 35 dB

RE-USABLE EAR PLUGS C€



CODE: EG3301B

- Hi-visibility blue triple flange TPR ear plugs
- H=28 bB, M=25 dB, L=25 dB)
- SNR 28 dB



CODE: DR-090CDET

- Hi-visibility fluorescent blue triple flange TPR ear plugs with detectable bearing
- H=33 dB, M=30 dB, L=28 dB
- SNR 32 dB



CODE: DR-118C

- Hi-visibility fluorescent blue triple flange TPR ear plugs
- H=31 dB, M=28 dB, L=27 dB
- SNR 31 dB



CODE: DR-090C

CODE: DR-090CI

DR-090C & DR-090CI (Corded & Plastic Box)

- Hi-visibility fluorescent green triple flange TPR ear plugs
- (H=33 dB, M=30 dB, L=28 dB)
- SNR 32 dB

EAR MUFFS



CLASSIC EAR MUFF

CODE: CEM

- · Padded headband ear muff with soft foam cushions
- · Low risk of entanglement on machinery
- · Hearing protection for extended periods
- Durable self adjusting ABS cups
- · Close fitting wire headband
- H=33,9 dB, M=26,4 dB, L=17,7 dB
- SNR 28,6 dB



CODE: JM-B

CE

- · Banded ear muff with soft foam cushions
- Adjustable rotational ABS cups
- · Lightweight & robust design
- Suitable for light industrial duty & outdoor construction
- H=28 dB, M=23 dB, L=15 dB
- SNR 25 dB

BUSHMASTER

CODE: BUSH-WG / BUSH-PC

- · Twin point mounted, adjustable ABS cups and soft foam cushions
- Hearing protection for extended periods
- · Visor can easily flip up and down
- Close fitting wire headband for comfort
- H=36 dB, M=27 dB, L=18 dB
- SNR 30 dB
- Replacement visors sold separately:

Gause: BUSH-BWGVISOR Polycarbonate: BUSH-BPCVISOR

INTEREX

CODE: INTEREX

CE

- EU slotted
- Unique DROMEX connector that fits all hard hats
- Large twin point mounted cups with soft foam cushions
- Easy to attach & detatch with spring loaded arms
- Steel arms maintain a constant & even pressure
- Adjustable cup for optimum comfort & fit
- H=31 dB, M=26 dB, L=19 dBSNR 28 dB













ORDER OF MARKING ON OCULARS WHERE RELEVANT:

















Scale number (filters only)

Makers mark

Optical class

Mechanical strenath

resistance

Fog resistance

Radiant heat

ORDER OF MARKING ON FRAMES WHERE RELEVANT:



Makers mark







The Standard Fields of use

Mechanical strength

LENS SELECTION AND APPLICATION:

Clear	general indoor use	eye protection against impact hazards
Grey	sunglare 5-2,5	Outdoor anti-glare lens use to prevent eye fatigue from sun glare
Amber	uv 2-1,2	Prevention of high density light (hdl) for contrast and rotational clarity
Green	sunglare 5-2,0	Prevent eye fatigue from indirect light flash
IR green	infrared 4-IR3 or 5	Used for certain welding & gas cutting techniques
Mirror	sunglare 5-1,7	Indoor/outdoor (i/o) for artificial and sunlight glare
Blue	sunglare 5-2,5	Outdoor anti-glare lens use to prevent eye fatigue from sun glare



FIELD OF VISION (OPTICAL CLASS)

OCULAR (1-3)

1 - ± 0, 06 DIOPTRES

 $2 - \pm 0$, 12 DIOPTRES $3 - \pm 0$, 25 DIOPTRES PERMANENT WEAR OCCASIONAL WEAR

EXCEPTIONAL WEAR

Optical class 1, 2 or 3 - indicates optical quality of the ocular and the wear duration



ROBUSTNESS

FRAME AND OCULAR are required to withstand specified lateral and frontal impacts at specified speeds



AGEING

FRAME AND OCULAR stability at elevated temperatures and ultraviolet radiation (oculars only)



HIGH SPEED PARTICLES	OCULAR (6mm STEEL BALL (0 86g))
- LOW ENERGY	45 m/s

120 m/s

Χ

B - MEDIUM ENERGY A - HIGH ENERGY 190 m/s S – INCREASED ROBUSTNESS (See optional below)

Χ

Χ



OTHER FIELDS OF USE:

	3 – LIQUIDS	Liquid droplets for goggles Liquid splash for face shields but not mesh		Х	Χ
	4 – LARGE (COARSE) DUST P	ARTICLES for goggles		X	
	5 – GAS & FINE DUST PARTIC	CLES		X	
4	8 – SHORT CIRCUIT ELECTRIC Face-shield to comply with a f and have a minimum thickness	filter of scale number 2-1,2 or 3-1,2			X
	9 – MOLTEN METAL & HOT So Both the frame and ocular sha with one of the symbols F, B o	all be marked with this symbol together		X	X
	K – GAS & FINE PARTICLE DA	MAGE			Х
	N – RESISTANCE TO FOGGIN	G (8 seconds)	X	X	Х
	G – RADIANT HEAT (EN 1731)			Χ	
	S – INCREASED ROBUSTNES	S (22mm ball at 5, 1 m/s)	Х	X	Χ
	-	er F, B or A to indicate that the eye protector article classification at extremes of temperature	X	Х	Х



ANTI-SCRATCH

Optional anti-scratch coating to protect the eye protector





Available frame colours:

CODE: DV-353C-AFL

CODE: DV-353C-AFB

- Polycarbonate mono lens, multi colour frame & rubber temples
- · Scratch resistant & Anti-fog lens

CODE: DV-353C-AFR

• Suitable Use: Construction, mining, instrument installations & warehousing

SPORTY COOL



Available frame colours:

- CODE: DV-894G-AF-R
- CODE: DV-894G-AF-B
- CODE: DV-894G-AF-Y
- · Polycarbonate mono lens, multi colour frame & rubber temples
- Scratch resistant & anti-fog lens
- Suitable Use: Outdoor use for glare, forklift drivers, & construction

FOCUS





CODE: DV-098C-AF

- · Polycarbonate mono lens, multi-coloured nylon frame & temples
- Scratch resistant & anti-fog lens
- Soft nose seat for comfort
- Suitable Use: Construction, instrument installations, general industry

SPORTY RACER



Available lens colours:



- Polycarbonate dual lens, black nylon frame & adjustable temples
- Soft nose seat for comfort
- Scratch resistant & anti-fog lens
- Grey: Anti-glare lens
- Suitable Use: General industry & safety officers.

Grey - Outdoor & construction environment

CLASSICS





SPORTY





Available lens colours:

CODE: DV-12C / AF

CODE: DV-12G

CODE: DV-12A-AF

CODE: DV-12GN

CODE: DV-12M (Mirror)

• Polycarbonate frame & mono lens, wide black frame & vinyl temples

· Scratch resistant lens

· Clear & Amber: Anti-fog lens

· Mirror, Green & Grey: Anti-glare lens

 Suitable Use: Construction, mining, milling, engineering workshops, factories, general industries, warehousing

EURO





Available lens colours:

CODE: DV-026-C / DV-026-C-AF

CODE: DV-026-G

CODE: DV-026-A

CODE: DV-026-GN

• Polycarbonate mono lens, black nylon frame & adjustable temples

· Scratch resistant lens

• Anti-fog lens (clear only)

• Anti-glare lens (amber, grey & green)

• Suitable Use: Construction, mining, milling, engineering workshops, factories

WELDING



CODE: DV-026-IR3 / IR5

• Polycarbonate mono lens, black nylon frame & adjustable temples

Scratch resistant lens

Suitable Use: Welding industry



IR3















Available lens colours:



CODE: DV-326B-C-AF




CODE: DV-326B-G-AF

- Used as a spectacle or a goggle all in one!
- Prescription lens inner attachment
- Polycarbonate mono lens & soft rubber face seal
- Efficient indirect ventilation system
- Detachable black polycarbonate adjustable temple
- Detachable 12mm adjustable elasticated headband
- Anti-fog & scratch resistant lens
- Suitable Use: General industry, light chemical splashes

SPOGGLE













CODE: DV-004MAX

- Clear (EN 170 2-1,2) polycarbonate mono lens
- 25mm Elasticated & adjustable headband
- High quality PVC frame
- Wide face contact area for comfort & seal
- Efficient indirect ventilation system
- Suitable with prescription spectacles
- Anti-fog lens & scratch resistant lens
- Suitable Use: Grinding, woodwork, light chemical splashes

MAXI VIEW GOGGLES





















CODE: DV-GW5

- · Shade 5, flip-up, polycarbonate mono lens
- Soft rubber face seal
- Efficient indirect ventilation system
- 11mm Adjustable elasticated headband
- Scratch resistant lens & anti-mist lens
- Suitable Use: Welding industry & applications

WELDING GOGGLE





WRAP AROUNDS





Available lens colours:

CODE: DV-1C

CODE: DV-1A

CODE: DV-1GN

- Polycarbonate mono lens & temples with ventilation
- Can be used with prescription spectacles as an over spectacle
- · Amber & Green: Anti-glare lens
- · Scratch resistant lens
- Suitable Use: Overspecs & visitors glasses

WIRE MESH



EN 1731

CODE: DV-504

- Metal wire mesh dual lens
- Clear polycarbonate & removable side protectors & vinyl adjustable temples
- Suitable Use: Forestry, woodwork, carpentry, mining

ACCESSORIES

- BLACK POUCH BAG (CODE: F-POUCH)
- GREEN RETAINER CORD (CODE: 8A-G)
- BLACK RETAINER CORD (CODE: 2803-W)









CAMO

CODE: 52J





- X1XXXX High cut & abrasion resistance
- High contact heat protection
- High dexterity
- Colour UV resistant
- Lint free & washable
- 100% Dromex Cut5 fibre
- Seamless ergonomic liner
- Ultra grip PU anti-slip coating
- Reinforced thumb crotch
- Composite knitted wrist

Suitable Use:

· Military & police, outdoor hunting, mining & extraction, search & recovery

Sizes: 8 - 11



NITRILE COATED

CODE: #57

EN 388:2016 + A1:2018



4X43C

- High cut & abrasion resistance
- High contact heat protection
- High grip power
- Colour UV resistant
- 100% Dromex Cut5 fibre
- Ultra grip Nitrile coating
- Composite knitted wrist
- Colour UV resistant
- Lint free & washable

Suitable Use:

Automotive, glass industry steel industry, chemical handling, oil & gas

Sizes: 7 - 12



LATEX COATED

CODE: 59YSP



3X43D

- High cut & abrasion resistance
- High contact heat protection
- High cut resistance
- High grip power
- Colour UV resistant
- 100% Dromex Cut5 fibre
- Ultra grip crinkle Latex coating
- Seamless ergonmic liner
- Composite knitted wrist
- Lint free & washable

Suitable Use:

Automotive, glass industry, steel industry, welding industry

Sizes: 8 - 11



SEAMLESS

CODE: 55M-Y





454X X2XXXX

- High cut & abrasion resistance
- High contact heat protection
- Colour UV resistant
- Lint free & washable
- 100% Dromex Cut5 fibre
- Seamless ergonomic liner
- Reinforced crotch area
- Composite knitted wrist

Suitable Use:

Automotive, glass & steel industries, welding

Sizes: 7 - 10













543 X2XXXX

- 100% Dromex Cut5 fibre
- HCT Nitrile multilayer technology
- Soft organic cotton inner liner
- H201B has extended cuffs
- **H201PLUS** 35cm cut resistant liquid chemical glove
- High cut & abrasion resistance
- General chemical resistance
- High contact heat resistance
- Colour UV resistant
- · Lint free & washable

Suitable Use:

- Automotive industry
- · Glass industry
- · Steel industry
- Machining & welding industry
- Oil & gas environments
- · Recycling & waste environments
- Mining extraction industry

Sizes: 10 (H201B)

8 to 10 (H201PLUS)



CODE: 57H201PLUS

MECHANICAL

NEW

CODE: HFM305







OEKO-TEX® STANDARD 100

4543

4X43C CUT

- HCT Nitrile multilayer coating on palms & fingers
- Excellent grip & resistance to oil
- Reinforced thumb crotch
- High cut & abrasion resistance
- High dexterity
- High tear & puncture resistance
- Compliant with OEKO-TEX® standard 100

Suitable Use:

- · Automotive industry
- Glass industry
- Steel industry
- Mining
- Oil & gas environments
- Construction
- Mild chemical handling

Sizes: 8 - 10













CODE: 50-135-TY (35cm)

FOOD SERIES

CODE: 55LF



- 100% Dromex Cut5 fibre
- FDA & German food grade approved
- Seamless with a composite knitted wrist
- Ambidextrous
- High cut & abrasion resistance
- Contact heat protection
- · Colour UV resistance
- Sanitised treatment
- Extra length
- · Lint free & washable


Suitable Use:

 Food processing, boning & carving, fsh filleting, meal preparation, food handling

Sizes: 7 - 11

(*Note these gloves are sold as individual units)

SLEEVES



- 100% Dromex Cut5 Fibre sleeve with thumb hole
- High cut & abrasion resistance
- High contact heat protection
- Colour UV resistant
- Lint free & washable

Sizes:

One size fits all

Suitable Use:

- Automotive industry
- Glass industry
- Steel industry
- · Machining & welding
- · Construction industry
- Mining & extraction industry

(Note these items are sold as individual units)



MACH30WP

CODE: MACH-30WP

EN 388:2016 + A1:2018



- · Hi-Viz Cut5 Mechanical glove
- · Multi function
- Impact resistant
- Anti-vibration
- Checker palm for grip
- Waterproof
- Latex foam reinforced multi-colour TPR back of hand impact protection

Suitable Use:

- · Heavy machinery
- Mining industry
- · Oil & gas industry
- Automotive/aerospace
- · Packaging/assembling
- Drilling

Sizes: 8 - 11



MACH MECHANIC

CODE: MACH100WP

EN 388

- · Hi-Viz Cut5 Mechanical glove
- Waterproof
- Impact resistant
- Anti-vibration
- Oil repellant fabric
- Kevlar fabric patch & anti-vibration patch on palm
- Latex foam reinforced multi-colour TPR back of hand impact protection

Suitable Use:

- Heavy machinery
- Mining industry
- Oil & gas industry
- Automotive/aerospace

Sizes: 8 - 11









IMPACT

CODE: 52LSTPV

EN 388



- 100% Cut5 fibre
- Innovative TPV impact protection
- PU dipped palm
- · Seamless ergonomic liner
- Velcro closing for enhanced fit
- · Composite knitted wrist
- · High abrasion & puncture resistance
- High cut & tear resistance
- · High impact protection
- TPV impact protection
- · Enhanced dexterity & flexibilty
- Good grip

Suitable Use:

- Oil & gas industry
- · Industrial handling & packaging
- Automotive industry
- · Construction & landscaping
- Assembly industry & plants
- · Heavy machinery equipment operations

Sizes: 8 to 10

MACH 777

CODE: MACH-777

EN 388



4444CP

- Cut5 HDPE lining
- High impact, abrasion, cut & tear resistance
- Black Nitrigrip & vibro-impact reinforced palm
- Grey back with black/lime IMPACT knuckle guard
- 7cm waterproof neoprene cuff with reflective tape
- Hi-Viz TPR on back of fingers & thumb
- Foamed padding on palm for anti-vibration
- Multifunctional mechanical glove

Suitable Use:

- · Heavy machinery
- Mining
- Automotive
- Packaging & warehousing

Sizes: 7 - 13





TECHNOLOGY

UNDERSTANDING THE NEW GLOVE STANDARD

You may have heard about the new glove standard but not quite sure what it means or how it's going to affect you.

Let's unpack what's changed by comparing the old to the new, explain the new testing methods and show you what to expect from the new glove markings.

OLD vs NEW

The new EN 388:2016 standard released in November 2016 has replaced the old EN 388:2003 glove standard in Europe.

Testing on resistance to abrasion, tear and puncture are carried out as they were before with minor clarifications to testing procedures and materials. The test results correspond the same way they did in the 2003 version with ratings of 0-4, with 4 being the highest performance level.

The main difference in the 2016 edition is in relation to cut resistance and impact protection. The new version now includes a TDM blade test in addition to the existing Coup Method and a test for impact resistance.

Existing Cut Test - Coup Method:

Under the EN 388 glove standard, introduced in 2003, cut resistance is measured with a Coup Test machine. A section of fabric is placed in a holder and a rotating circular blade is moved back and forth at a constant speed, pressing down with a force of 5 Newtons. When the blade cuts through, a performance rating from 1 to 5 is calculated from the total distance of travel. The blade gradually loses sharpness, so at the start and finish it is calibrated using cotton fabric. Therefore, the result can be less accurate for gloves with a higher cut-resistance. This test method remains in the 2016 version but is only to be used for materials that do

not affect the sharpness of the blade.

Additional New Cut Test - TDM blade test:

TDM is an abbreviation for the equipment used to conduct this test, a tomodynamometer. This test involves a straight blade being drawn across the sample in one movement, with a new blade every time. The 'stroke length' before cut-through is recorded for a range of forces and graphs plotted to predict the force required to cut through the glove in 20mm of travel. This force is used to calculate a score from A to F, with F being the highest rating.

Impact Testing

Impact verification has been added to EN 388: 2016. The test method is taken from the motor cycle standard EN 13594:2015.

The area where the impact protection is claimed to be tested, but due to technical reasons, the area around the fingers cannot be tested.

If the requirements are fulfilled, the glove will be marked with a P (Pass). If the glove fails, there will be no marking.


HOW DOES THIS AFFECT YOUR CURRENT GLOVES?

EN 388:2016 supersedes EN 388:2003 BUT it only affects new product certification and will not apply retrospectively.


Gloves may continue to be sold under both versions of the standard until 2023 when, under the new PPE regulation, certification will need to be renewed to the latest version of the standard.

GLOVE MARKINGS

EN388:2003



EN388:2016



Know Safety. No Injury. Know Dromex.

Copyright © 2019 Dromex CC, South Africa. All rights reserved.





INFERNÖ

CODE: INFERNO

- Tan leather multi-layered fire fighters glove
- · High breathability
- High heat resistance
- High temperature stability
- High abrasion resistance
- PU moisture barrier
- Multi-layer protection provides flexibility, comfort & excellent insulation

Sizes: M - XL

Meets with the requirements of NFPA 1971:2013 Edition: Standard on Protective Ensembles for Strucural Fire Fighting.

- Gunn cut wing thumb with reinforced index & middle finger palm
- Knitted cuff with continuous pull & shirred back
- Multi-layer: hand layer is knitted composite modacrylic para-araid fibre with a non-woven urethane vapor barrier. Finger tacked.
- Tan split cow leather palm 1.0 to 1.2mm with equivalent reinforcing
- Tan split cow leather back 1.0 to 1.2mm, shirred
- Yellow aramid knitted wrist cuff with tan split cow leather 0.8 to 1.0mm leather continuous pull

- Structural & wildland fire fighting applications
- Search & rescue



IRON MAN

CODE: S-H33

EN 388



3544X



- Kevlar palm & aluminium back with Kevlar lining
- · High heat resistant with cotact heat up to 500°C
- Protection against molten metal sparks & splash
- 100% Cotton with PU foam cotton liner
- Excellent resistance to abrasion, cut & tear
- Excellent grip
- 360g per glove

Sizes: 10

Suitable Use:

- Foundry
- Forging
- Welding
- Furnaces



MOLTEN WARRIOR

CODE: S-H35



3444X



/

- Leather palm & aluminium back with Kevlar lining
- High heat resistant with contact heat up to 500°C
- Protection against molten metal sparks & splash
- 100% Cotton with PU foam cotton liner
- High resistance to abrasion, cut & tear
- Excellent grip in oily conditions
- 398g per glove

Sizes: 10

- Foundry
- Forging
- Welding
- Furnaces







CHEMICAL NITRILE

CODE: 0056







- Green Nitrile unsupported (0.38mm) thick
- Micro flock lined for comfort
- Textured palm, fingers and partially on the wrist for grip
- Washable
- Straight cuff
- 33cm length
- Resistant to
 - K: Sodium Hydroxide 40%
 - L: Sulphuric Acid 96%
 - J: n-Heptane

Sizes: 6 - 10

- Chemical handling as per EN 374
- Chemical processing
- Oil refining petrochemicals
- Mild acids
- Solvents
- Oils & greases
- Food processing
- Automotive assembly
- Painting & maintenance



ULTI-CHEM

CODE: ULTICHEM









- Triple coated, lightweight nitrile glove with micro foam palm
- Protection against chemicals, mechanical & micro-organism risks
- Excelent dexterity & grip
- FDA (Food & Drug Administration) accredited
- Resistant to:
 - A: Methanol
 - J: n-Heptane
 - K: Sodium Hydroxide 40%
 - L: Sulphuric Acid 96%

8 - 10 Sizes:

Suitable Use:

- Chemical handling as per EN 374
- Cleaning industry
- Janitorial industry
- Environmental clean-up





CODE: ULTICHEMPLUS

EN 374-2 EN 374-1













- · Premium protection against chemicals, mechanical, contact heat & micro-organism hazards
- High cut performance Polyethlyene, glass fibre, spandex
- Triple coated, lightweight nitrile glove with a mirco foam finish
- Exellent dexterity & grip
- FDA (Food & Drug Administration) accredited
- Resistant to:
 - J: n-Heptane
 - K: Sodium Hydroxide 40%
 - L: Sulphuric Acid 96%

8 - 10 Sizes:

- Chemical handling as per EN 374
- Laboratories
- Sheet metal handling
- Assembly work & automotive









CODE: VIPER / VIPERPLUS







- Viper: 35cm length | Viper Plus: 60cm length
- Protection against chemicals, mechanical risks & micro-organisms
- Double dipped PVC
- Textured palm for grip in wet & oily conditions
- Comfortable cotton liner
- High abrasion protection & tear resistance
- Impermeable protection
- Resistant to:
 - A: Methanol
 - J: n-Heptane
 - K: Sodium Hydroxide 40%
 - L: Sulphuric Acid 96%



Sizes: 9 - 10

- Chemical handling as per EN 374
- Petrochemical
- · Assembly & metal fabrication
- Waste water & water treatment



OIL-TECH

CODE: DG-OIL-TECH



- Double dipped & fully coated nitrile glove
- · Protection against mechanical risks
- · Superior dexterity
- Textured palm for grip in wet & oily conditions
- 13-Gauge comfortable seamless nylon liner
- High abrasion protection & tear resistance
- Provides liquid protection & water resistant

Sizes: 8 - 11

- Oil & gas industry (OGP)
- Mining & extraction
- · Heavy machinery
- Aerospace
- Mechanical workshops
- · Automotive
- Precision engineering applications







THOR ELECTRICAL INSULATING GLOVES

CODE: DG-THOR

AC (alternating current)
RC category PN-EN 60903:2006
(EN 60903:2003 + AC2:2005)





- Exclusively for electrical purposes
- R acid resistant, oil resistant, ozone-resistant
 C resistant to extremely low temperatures
- · High quality rubber latex
- · High flexibility preventing hand fatigue
- Fits well when worn with protective leather over gloves
- Each glove is electrically tested & issued with an examination certificate
- 360mm (±15mm) long

Sizes:

- Class 0 2: 8 10
- Class 3: 9 & 10

Available in four classes defining voltage requirements:

CLASS 0 > 0 (5kV), Low voltage

CLASS 1 > 1 (10kV), High voltage

CLASS 2 > 2 (20kV), High voltage

CLASS 3 > 3 (30kV), High voltage

Suitable Use:

• Electrical purposes, installation, maintenance & repairs

LEATHER OVER GLOVES

CODE: DG-OV

EN 388:2016 + A1:2018





- Designed to protect the Thor electrical insulating gloves from potential hazards such as cut, abrasion, tear, puncture & flame.
- Can also be used as mechanical gloves, worn directly over the hands for non-electrical / arc applications
- Adjustable Velcro strap ensuring secure fit
- · Waterproof cow grain leather with Kevlar thread
- High resistance to flammability
- Highly flexible & durable

Sizes: S/M L/XL

- Electrical purposes, installation, maintenance & repairs
- · Mechanical applications



NITRIFLEX



- High abrasion
- Strong oil-resistance
- Super grip
- Softer touch & higher flexibility
- 100% Nitrile micro foam finish
- Nylon blended spandex liner
- Innovative fibre
- Composite knitted wrist
- Sanitised



CODE: NITRIFLEX

Sizes: 7 - 11

Suitable Use:

- General maintenance (indoor & outdoor)
- Assembly work (indoor & outdoor)



CODE: NITRIFLEXPC





NITROLITE

CODE: NITROLITE

EN 388

4131

- High abrasion
- Oil solvent resistance
- High dexterity
- Grey nitrile palm coated
- Nylon seamless shell
- Composite knitted wrist

Sizes: 7 - 10

Suitable Use:

- **Engineering assembly**
- Workshops
- General handling



CHAIN MAIL

CODE: RTCMG-01

DIN EN 1082-1

- Stainless steel chain mail glove
- **Ambidextrous**
- Wrist length
- Washable
- Tapered fit design
- 20mm Colour coded fastening wrist band
- Supplied with glove tensioner

Sizes: XS - XL (Colour of band differs per size)

Suitable Use:

- Bandsaw
 - Straight edge cutting machine operation
- Abattoir
- Meat & poultry & butchery







- Ultra thin for comfort & tactile sensitivity
- Ambidextrous
- Eliminates fingerprints & scratches
- Reduces perspiration on palms
- Composite knitted wrist
- Dust & lint retardant
- Washable & reusable

8 - 10 Sizes:

- · Automotive industry
- Glass & steel
- Chemical handling
- Oil & gas





CODE: MIIZU300HI



CODE: MIIZU300BLU

NEW

MIIZU 300

EN 388 4131X

- High visibility
- High durability
- High dexterity
- Super grip
- Waterbased PU & Nitrile micro foam finish
- Composite knitted wrist

Suitable Use:

- Automotive assembly
- Component assembly
- Packing assembly
- General handling

Sizes: 8 - 11

MIIZU 400 THERMAL

CODE: MIIZULFM4001W



+ A1:2018



2232X



EN 511:2006

- High visibility
- Soft yellow polyester glove with poly-acrylic fleece lined fibre
- Micro foam latex palm & fingers for excellent grip
- Good abrasion, puncture, tear & cut resistance
- Functions at temperatures up to -50 °C

Suitable Use:

- Cold storage
- Outdoor winter applications
- **Fisheries**
- Logisitics

Sizes: 8 - 10



CODE: PU2001B



CODE: PU2001

PU20.01

EN 388



- High durability
- High dexterity
- Super grip
- Protection against abrasion
- 100% Polyurethane palm & finger coating
- 100% Nylon seamless liner
- Composite knitted wrist

Suitable Use:

- Automotive & machining
- Component assembly
- Packing assembly

6 - 10 (PU2001B) • 6 - 11 (PU2001) Sizes:



MACH IMPACT

CODE: MACH-2WP15

EN 388



- Maximum dexterity & high grip performance
- Back of hand impact protection
- Provides optimum balance between flexibility & impact dispersion
- Waterproof

Suitable Use:

- · Oil & gas industry
- · Industrial handling & packaging
- · Mining industry
- · Automative industry
- Construction & landscaping
- · Assembly industries & plants
- · Agriculture industry
- · Heavy machinery equipment

Sizes: L



MACH MINERS

EN 388



- Impact absorbing & 3 dimensional protection
- Thermo plastic rubber on back of fingers & thumb
- · Anti-slip palm
- Highly reflective knuckle strip with an ergonomic design reducing hand fatigue
- Multi-functional protection



Suitable Use:

- Mechanics
- · Strip miners
- Machine & equipment operators
- General warehousing

Sizes: 8 - 12 (MACH4)

8 - 11 (MACH6)



CODE: MACH-6 (WATERPROOF)

MACH DURA GRIP

CODE: MACH-5

EN 388



- Multi-functional anti-vibration mechanical glove with finger, thumb, palm & back protection
- Maximum dexterity & non-slip performance
- Synthetic leather palm & durable anti-slip PVC patches
- Strengthened palm for gripping power in slippery conditions
- High visibility composite Poly/Spandex knitted fabric

- Optimum balance between anti-slip & protection for back of hand
- Double stitched black triangular indent pattern PVC palm, index & thumb patch
- Black form fitting leatherette palm & knuckle area
- Fluorescent yellow spandex back
- Velcro elasticated wrist strap

Suitable Use:

- Outdoor machinery
- Mining
- Automotive

Sizes: 9 - 10







PU₅

CODE: PU5

EN 388



- High mechanical strength
- Cut level 5 (EN 388:2003)
- Cut level 4 & C (EN 388:2016)
- Superior dexterity & grip
- · High tear resistance
- Protection against abrasion, cut & puncture hazards
- PU Coated palm & fingers
- HDPE Liner

Sizes: 7 - 10

Suitable Use:

- Automotive industry
- Component assembly
- Packaging
- Warehousing



SUPERLITE

CODE: PU20.02

EN 388



- · High durability
- · High dexterity
- Super grip
- High sensitivity on the fingers area
- PU Coated palm & fingers
- Blue seamless light nylon liner
- Innovative fibre
- · Composite knitted wrist

Sizes: 8 - 11

Suitable Use:

- General maintenance
- · Assembly work
- Fine assembly work
- Small component handling



ANTI-STATIC

CODE: PU20.07E

EN 388



- Anti-static
- · High durability & dexterity
- Super grip
- High sensitivity on the fingers area
- PU Coated palm & fingers
- White seamless light nylon liner
- Innovative fibre
- Composite knitted wrist

Sizes: 7 - 10

Suitable Use:

- Assembly where static discharge has to be avoided
- Computer & circut board work
- Automotive cluster work



DYTEC

CODE: DYTEC

EN 388



- Cut level 3
- High durability & dexterity
- Super grip
- High sensitivity on the fingers area

- PU Coated palm & fingers
- 100% Dytec3 seamless light liner
- Innovative fibre
- · Composite knitted wrist

Suitable Use:

- · Coal mining
- · Working with shale or sharp rocks

Sizes: 8 - 11





COTTON GLOVES



CODE: DH100



CODE: GCOT



CODE: GCOT/DD



CODE: GCOT/W-L

COATED GLOVES





CODE: 1412A



CODE: GFREEZER/OC



CODE: NITRILE 0722



CODE: NITRILE 0742



CODE: NITRILE 0921



CODE: DH0911A



CODE: CRONUS/E



CODE: CRONUS/RGE



CODE: GCRAY



CODE: CRONUS/RGW



CODE: CRONUS/W



COATED GLOVES



CODE: GPVC/27/HG



CODE: GPVC/40/HG



CODE: GPVC/27



CODE: GPVC/KW



CODE: GPVC/35



CODE: XTRA/27



CODE: XTRA/KW



CODE: XTRA/35



CODE: GCOM/KW



CODE: GLATEX/35



GLOVE ACCESSORY

CODE: GCLIP

RUBBER, LATEX & NITRILE GLOVES



NITRO SHIELD

CODE: DG-NITS

EN ISO 374-5:2016 EN 374-1 TYPE B







- 100% Nitrile which prevents allergies
- Disposable & powder free
- Lightweight yet strong due to the glove construction
- Comfortable and good dexterity
- · Food safe and chemical resistant
- Beaded cuff for easy putting on & taking off in addition to offering drip protection for the forearm
- · Biodegradable
- Ambidextrous
- FDA compliant

Sizes: S - XL

Suitable Use:

 Mild chemicals, bacteria, fungi, viruses & food products.

LATEX RUBBER GLOVES



CODE: H2-55



CODE: H1-40



CODE: DG-HS-B



CODE: H2-40

HOUSEHOLD GLOVES



CODE: DG-HS-Y




LEATHER WELDING GLOVES

WELD/PME

WELD PRIME

CODE: WELD/PRIME



- Premium cow split leather
- Reinforced thumb
- Yellow cotton fleece hand lined and black cotton woven cuff lining.
- 16 inch cuff for full hand protection
- Contact heat resistance up to 350 °C for 15 seconds
- EN Approved

Sizes: 10

Suitable Use:


· Welding related operations





WELD RED

CODE: WELD/RED



- Premium grade cow split leather
- Fully cotton lined palm and fingers
- Gunn cut, apron palm & wing thumb
- · Sewn with Kevlar thread

Sizes: 10

Suitable Use:

· Welding related operations

WELD BLUE

CODE: WELD/BLUE





- Premium A grade cow split leather
- A fully cotton lined palm and fingers
- · Gunn cut fingers and winged thumb
- Reinforced leather palm, fingers, knuckle and pull strap
- · Sewn with syntax thread

Sizes: 10

Suitable Use:

Welding related operations

LEATHER / WELDING GLOVES





CODE: GGOAT-15CMC



CODE: WELD/6



CODE: WELD/2.5



CODE: GCANDY



CODE: GTIG/ECONO



CODE: GTIG



CODE: GGOAT



CODE: GRIGGER/EXEC



CODE: WELD/16GR



CODE: WELD/2.5GR



CODE: WELD/6GR



CODE: 88PBSA



CODE: G5





PROMAX DISPOSABLE COVERALL

CODE: PROMAX













- Type 5 and 6 disposable coverall
- Microporous spun bound polyproplene and polyethylene laminate fabric with bound seams
- Zip and storm flap front closing
- Non-linting
- Good mechanical properties and performance
- Protects the arms, legs, torso and head from the hazards of light liquid sprays, chemical splashes and sprays, airborne solid particulates and anti-static dissipation
- Liquid penetration resistance against a basic range of chemicals:

Sulphuric Acid 30% - Class 3 Sodium Hydroxide 10% - Class 3 O-Xylene – Class 3 1-Butanol – Class 3

Sizes: Small – 3XL

- Pharmaceutical
- Food processing
- Asbestos removal
- Accident attendance
- Fiber exposure
- · Painting and spraying
- Clean rooms
- · General maintenance







PROMAX 1000 DISPOSABLE COVERALL

CODE: PROMAX-1000





- A breathable microporous polyethylene with spunbond polypropylene composition that has excellent physical properties (strength, elasticity, tear etc)
- Enhanced waterproof performance providing impervious protection suitable for use against biological hazards
- All seams are taped for additional strength and protection especially against dangerous airborne particles & liquid
- Resistant to:

GB 19082-2009, clause 5.4 – Water penetration

GB 19082-2009, clause 5.4.3 – Penetration by synthetic blood

GB 19082-2009, clause 5.7 – Filtration efficiency

GB 19082-2009, clause 5.10 – Electrostatic decay properties

Sizes: M-XL

Suitable Use:

· Industrial & medical environments



PROMAX C4000 **DISPOSABLE COVERALL**

CODE: PROMAX-C4000























- Type 3, 4, 5 & 6 disposable coverall
- Yellow polyproplyene and polyethylene foil fabric
- Ultrasonic welded & taped seams preventing permeation, dust & liquid ingress
- Double zip & storm flap for secure front protection
- Double elasticated cuff with thumb loop
- Double layer cushioned knee pads for comfort & durability
- Protects the arms, legs, torso & head from the hazards of light liquid sprays, chemical splashes & sprays, airborne solid $particulates, radioactive\ contamination, anti-static\ dissipation$ & infective agents contact
- Resistant to penetration by blood/fluids, wet bacterial penetration, biologically contaminated aerosols & powders
- Permeation and chemical penetration protection against a basic range of chemicals:

Sulphuric Acid 96% - Class 6 (Permeation)

- Class 3 (Penetration)

Sodium Hydroxide 10% - Class 3 (Penetration)

o-Xylene - Class 3 (Permeation)

1-Butanol - Class 3 (Penetration)

Sizes: S-3XL

- Chemical handling & distribution
- Chemial clean ups
- Contaminated land cleaning
- **Pathogens**
- Oil spills
- Tank cleaning
- Petrochemical
- Refining applications







NON WOVEN DISPOSABLE COVERALL

CODE: PDISPO




- Disposable full body coverall for protection against dust & fine particulates
- 50gsm Spunbond polypropylene
- Elasticated wrists, legs & hood
- · Nylon zipper front
- Lightweight

Sizes: M - 3XL

Suitable Use:

General maintenance









WHATEVER THE WEATHER WE HAVE YOU COVERED.

Working outdoors or in cold environments means that the elements can sometimes be against you but one thing you can be sure of is that the Dromex Storm range is always on your side.

Dromex Storm apparel has been formulated for endurance in some of the harshest environments including cold storage & refrigeration, outdoor contractor applications, outdoor security, agriculture, mining and even the petrochemical industry.

Every Storm jacket & suit has been made to ensure thermal protection, water resistance, high-visibility if required and include valued features for practicality, safety & comfort.

Our premium Hydro-Plus rain suit has been designed to offer protection from chemicals and has flame resistant & anti-static properties.

Whether the temperatures are low or there's wind, driving rain and unpredictable conditions, being assuredly safe, dry and warm is something you can count on.

We believe you're entitled to maximum protection without compromise and we make sure you always get it.



SFORM





APOLLO THERMAL JACKET

CODE: DB-APOLLO

- Bomber-style thermal protective & water-resistant jacket
- Outer: 280gsm Gabardine fabric
- Body lining: 240gsm 100% Polyester fleece fabric
- Sleeve lining: 100% Quilted Polyester 190T Taffeta & padding on sleeve: 180gsm 100% Polyester fabric
- 50mm Silver reflective tape on arms, waist & upper abdomen
- · Elasticated rib knit cuffs & waistband
- Detachable sleeves with open end nylon zip
- · Heavy-duty chunky nylon zip at front
- Two large side entry waist welt pockets
- Right breast pocket: a dual utility bellow pocket with flap Velcro closure and a chunky nylon closed end zip closure.
- Left breast bellow pocket: with storm flap Velcro closure and plastic ID card holder with Velcro closure.
- Internal right breast pocket with Velcro closure

Sizes: XS - 5XL

- Petrochemical
- Marine industry
- Agriculture
- Mining
- Outdoor & contractor applications
- Rain & wet conditions







SFORM

WETPRO THERMAL JACKET

CODE: DB-WETPRO-LNB

- 2-Tone lime/navy blue reflective jacket
- Thermal protective & water-resistant storm jacket
- · Composition:
 - Outer: 300D, 100% Oxford Polyester fabric
 - Lining: 100% Quilted Polyester 190T Taffeta fabric
 - Padding: 100% Polyester fabric
 - Storm cuff: 100% Polyester rib knit fabric
- Jacket includes a fixed stow away hood with drawstring fasteners & Velcro closure
- Heavy-duty chunky nylon zip, outer storm flap with large nylon press studs
- 2 Waist jet pockets with large straight cut flaps
- Utility/accessory bellow pocket with Velcro closure on right breast
- Internal left breast with patch pocket & nylon zip
- 50mm Silver reflective tape on arms, wrist, shoulders, waist & breast
- Inner jacket water drainage system

Sizes: XS - 5XL

- Petrochemical
- Marine industry
- Agriculture
- Mining
- Outdoor & contractor applications
- Rain & wet conditions







SFORM

LITE WINDBREAKER

CODE: DB-STL

- Thermal protective hooded jacket
- Outer: 100% Polyester, 210T Fabric with PU coating
- Inner: 240gsm Polar fleece
- Sleeve: 160gsm Cotton with 190T Taffeta
- Fixed hood with drawstrings
- Heavy-duty nylon zip with metal puller
- · Two side entry pockets with reflective trim
- Left breast pocket with press stud closure

Sizes: S - 3XL

Suitable Use:

- Cold/wet outdoor environments
- Cold storage & refrigeration



NB





HYDROPLUS RAIN SUIT

CODE: DB-HYDROPLUS

Designed to:













- 30% PVC, 60% Polyurethane & 10% Polyester, 310gsm fabric
- Premium rainsuit suitable for exposure to rain
- Fluorescent orange high visibility garment with 50mm silver reflective tape on arms, legs & torso and has flame resistant & anti-static properties
- Lightweight, water-resistant & comfortable
- Semi-opened rear and lined with polyester for breathability
- Heat sealed seams
- Jacket collar includes a fixed stow away hood compartment with drawstring fasteners
- Raglan sleeves with eyelets for aeration at armholes
- Heavy-duty chunky nylon zip, outer stom flap with large press studs and sleeves with storm cuffs
- 2 Large waist pockets with storm flaps
- Pants with elasticated waistband
- Ankle features press stud closures

Sizes: S - 3XL

- Petrochemical
- Marine industry
- Agriculture
- Mining
- Outdoor & contractor applications
- Rain & wet conditions







S\(\bar{F}\)ORM

GLACIER FREEZER SUIT

CODE: DB-STG-J/P

- Navy blue, 2-piece freezer suit
- Splash proof & lightweight
- Outer: 100% Polyester 210T Oxford fabric with PVC coating
- Inner: 300gsm Cotton with 190T Polyester Taffeta
- Jacket includes a fixed hood with drawstrings, a heavy-duty zip & elasticated sleeve cuffs
- Trousers have an elasticated waist, two side pockets
 & open cuff legs

Sizes:

Jackets: S - 3XL Pants: S - 3XL

- Cold storage & refrigeration
- · Outdoor work in cold climate
- Contractor applications



S\(\bar{F}\)ORM

POLAR THERMAL REFLECTIVE SUIT

CODE: DB-STP-J / P

- 2-piece thermal suit with 50mm silver reflective tape on arms, waist & legs
- Thermal protective & water-resistant
- Outer: 100% Polyester 300D Oxford with PVC
- Inner: Polyester Taffeta with Cotton
- Jacket includes a detachable hood with drawstrings & a heavy-duty non-metal zip with storm flap & press stud closure
- · Sleeves have an internal storm cuff
- Four utility jacket pockets with passants on shoulders with snap closure
- Pants have an elasticated waist with two side entry pockets
- · Ankles have zip closure with apron seal
- Fully taped seams

Sizes:

Jackets: S - 4XL Pants: S - 4XL

- Work in rain/wet /cold environments
- Mining
- Cold storage & refrigeration
- Outdoor work in cold climate
- Contractor applications
- Outdoor security





PVC RAIN SUITS



CODE: PRS70-Y *For contractors / short term use

HYDRO RAIN SUIT

CODE: DB-HYDRO

- · Recommended Product
- Heavy duty PVC coated rain suit with hood
- 85% PVC 15% Polyester
- · Jacket with fixed hood & drawstring closing
- Storm flaps over heavy-duty plastic zip with large plastic press stud closure
- Pants with elasticated waist and press stud closures on the ankles
- All seams are electro welded and stitched for durability
- · Comfortable to wear

Sizes: S-5XL



RUBBERISED RAIN COATS/SUITS







PVC STORM SUIT



STORM JACKET & BIP PANTS

CODES: JH-SM-G (JACKET)
BP-SM-G (BIB PANTS)

- Heavy duty PVC & Polyester inner lining, 481gsm
- Welded seams throughout for waterproof protection
- Jacket with fixed hood & drawstring, 2 pockets with storm flap, plastic double snap closure at the neck
- Sleeves with internal storm cuffs
- Bip pants have adjustable webbing suspender with plastic buckles
- · Jackets & Bib pants sold separately

Sizes:

Jackets: S - 3XL Bib Pants: S - 3XL

- General mining
- · Marine & fishing industry
- Outdoor & contractor applications
- Rain & wet environments





LEATHER APRONS



ARC & ACE APRONS

- Full or half length aprons with buckle closure, adjustable neck & waist strap
- Heavy-duty premium cow split leather
- Protects the worker's entire front of body

Suitable Use:

- Welding
- Maintenance
- Manufacturing
- Carpentry

TAEKI CUT5 CLOTHING



CODE: TAEKI JACKET*excludes neck protector




CODE: TAEKI APRON 60120

LEATHER CLOTHING & KIDNEY BELT


















FALL ARREST







FULL BODY HARNESSES

- Polyester full body harness with adjustable chest & leg straps
- Includes a Dorsal D-Ring for fall arrest
- Ideally placed sit strap for extended comfort
- Equipped with Lanyard Keepers for placement of free lanyards
- Weight capacity of 140kg (incl. tools)

DFA-PN10

 Includes shock absorbing double lanyard with steel scaffold hooks (DFA-PN361N) and 25mm chest strap

DFA-PN21

- Includes shock absorbing double lanyard with steel scaffold hooks (DFA-PN361N)
- Adjustable 44mm sliding chest strap, shoulder straps, leg straps and waist belt

Sizes: One Size

- Meets the requirements of the European PPE Regulation (EU) 2016/425
- Certified to EN 361:2002 and EN 355:2002

- Construction industry
- · Cleaning, painting & building maintenance
- Scaffholding applications
- Refineries
- Oil Rigs







FALL ARREST ACCESSORIES



DOUBLE SCAFF HOOK LANYARD

CODE: DFA-PN361N

CE

- Fall Arrest 44mm Forked Webbing Lanyard made from high tenacity polyester (1.75m length)
- Consists of Energy Absorber with loop and Steel Scaffold Hooks
- Allows movement in all directions while remaining safely anchored at all times
- Loops are protected by an abrasion resistant covering at the ends and prevents the webbing from being damaged by the metallic connector.
- Certified as per EN 355:2002









RETRACTABLE FALL ARRESTERS

CE

- Vertical length systems (DFA-PN2002)
- Vertical & horizontal length systems (DFA-TPGS15 and DFA-TPGS06)
- Colour impact indicators at attachment ends
- Certified as per EN 360:2002

ACCESSORIES





TWIN TOOL LANYARD
CODE: DFA-TL02



SUSPENSION INTOLERANCE STRAP

CODE: DFA-STS01



REFLECTIVE WEAR: GENERAL INFORMATION

To ensure that your reflective garment is effective it needs to conform to EN ISO 20471:2013.

What is EN ISO 20471?

EN ISO 20471 is a revised version of the previous EN 471 high visibility PPE standard. According to Directive 89/686/EEC, it requires by law to protect people who work on or near a roadside, whilst they go about their day to day business.

The standards are set by identifying the risks to people. This is the minimum standard for high visibility clothing, which is capable of visually signalling the user's presence and which specifies test methods and performance requirements for PPE worn in high-risk situations.

What is the main criteria for the standard?

Colour and retroreflection as well as for the minimum areas and for the placement of the materials in protective clothing. Three classes of garment are defined based on three different minimum areas of retroreflective, fluorescent and/or combined performance materials. Each of these classes will provide a different level of conspicuity.

Material	Class 3 Garments	Class 2 Garments	Class 1 Garments	
Background material	0,80	0,50	0,14	
Retroreflective material	0,20	0,13	0,10	
Combined performance material	n.a.	n.a.	n.a.	
NOTE: The clothing class is determined by the lowest area of visible material.				

Class 3 is the class that provides the highest degree of conspicuity against most backgrounds found in urban and rural situations in daylight and in night time. There are within the standard, certain requirements for in-use test requirements.

The standard takes into consideration the materials require brightness after:

Retroreflective Flourescent
Rainfall performance UV exposure

Temperature variation Dimensional change
Abrasion Water vapour resistance

Cold folding Colour fastness

Flexing Mechanical properties

Washing

Dry cleaning (where applicable)

REFLECTIVE VESTS





2-TONE REFLECTIVE JACKETS 100% POLYESTER TRICOT/MESH FABRIC

CODE: SA13-SL

SA14-NS (SLEEVELESS)

- Polyester & mesh fluorescent lime open weave fabric
- Reflective tape is 50mm silver bead industrial washing T/C tape
- · Nylon zip fastener with metal slider & buttons
- Identity card holder on left breast (SA13-SL only)
- Garment Class 2
- Enhanced visibility from all sides
- Detachable zip sleeves (SA13-SL)

Sizes: S - 3XL & 5XL

 Manufactured to ISO 20471:2013 (EN 471 & SANS 50471) as per requirements of 89/686/EEC.

- · Construction industry
- Warehouse environment
- Mining industry
- · Police/law enforcement

REFLECTIVE VESTS









FLAME RETARDANT REFLECTIVE VEST

CODE: SA003-FR

- Flame retardant vest made with 100% Polyester fluorescent lime open weave fabric
- Flame retardant tape is 100% Cotton woven fabric with micro-glass bead coating, 520g/m²
- Velcro closure
- Black Polyester binding
- Garment Class 2

Sizes: S-5XL

Suitable Use:

- Construction industry
- · Warehouse environment
- Mining industry

Compliancy

Tape: EN ISO 20471:2013 & EN 469:2005+A1+AC Fabric: ISO 6330:2012, EN ISO 14116:2008





FLAME RETARDANT & ANTI-STATIC REFLECTIVE VEST

CODE: SA11-ASFR

- Flame retardant & anti-static vest made with 96% Polyester fluorescent lime open weave fabric & 2% carbon thread
- Flame retardant tape is 100% Cotton woven fabric with micro-glass bead coating, 520g/m²
- Nylon zip fastener with metal slider
- Clear on black top entry plastic pouch
- Black Polyester binding
- Garment Class 2

Sizes: S-3XL

Suitable Use:

- Construction industry
- · Warehouse environment
- Mining industry

Compliancy

Tape: EN ISO 20471:2013 & EN 469:2005+A1+AC Fabric: ISO 6330:2012, EN ISO 14116:2008



REFLECTIVE VESTS



2-TONE MESH REFLECTIVE VEST

CODE: SA50Y-OR / YB

- 100% Polyester fluorescent yellow/navy or yellow/red knitted weave fabric
- 18mm Reflective tape retro-reflective silver glass beads
- Nylon zip with metal slider
- Clear PVC on black top entry plastic pouch/ID pocket

Sizes: S - 3XL

Suitable Use:

- Construction industry
- Warehouse environment
- Mining industry







2-TONE REFLECTIVE VEST

CODE: SA-2T

- Nylon black zip with metal slider
- · Clear PVC on black top entry ID pouch
- · White reflective tape

Sizes: S-5XL



MESH REFLECTIVE VEST

CODE: SA7B2

**MESH VENTILATION WITH PVC TAPE

- Nylon lime zip with metal slider.
- Clear PVC on black top entry ID pouch
- Space for branding on back of vest

Sizes: S-5XL

SA10 REFLECTIVE VEST

CODE: SA10-LIME

- · Nylon zip with metal slider.
- Clear PVC on black top entry ID pouch
- · Construction/warehouse/mining

Sizes: S-5XL



FIRE BLANKETS







GLASS FIBRE FIRE BLANKET

CODE: FBGF

Complies with requirements of EN 1869:1997

- 100% Glass fibre
- Heat resistant, light duty fire blanket designed to extinguish small incident fires
- Protects human lives & equipment from fire
- Withstands temperatures reaching 550°C
- Supplied in a red, clearly marked bag that can be hung on nearby walls for quick access

Sizes: 2m x 2m

Suitable Use:

- Household kitchen fires (oven & stove)
- · Extinction of fire on clothing
- Catering establishments/restaurants
- Training centres
- Hospitals & nursing facilities
- Laboratories
- Garage & workshops
- Retail outlets
- Flammable liquid cans
- Cinema projection rooms
- Office buildings



CERAMIC FIRE BLANKET

CODE: FBCER

- 1200°C Ceramic fibre cloth
- Low thermal conductivity
- · High temperature stability
- · Excellent tensile strength

Size: 2m x 2m

- Construction industry
- Warehouse environment
- Mining industry

WELDING SCREENS, FIRST AID KITS & THERMOMETER

Dromex 🔕

WELDING SCREENS

CODE: WELDSCR

- 100% Flame Retardant PVC
- Brass eyelets

Sizes:

2m x 2m 2m x 3m

Suitable Use:

- Construction industry
- · Warehouse environment
- Mining industry



FIRST AID KIT FA-3 & FA-7

- Emergency treatment for sick or injured
- White, portable & wall mountable steel box

Replacement Contents Available:

- FA-3/Refill
- FA-7/Refill

Suitable Use:

- Indoors
- Offices
- Manufacturing environment







Care Care

CODE: FA-3/REFILL



CODE: FA-7



CODE: FA-7/REFILL

INFRARED THERMOMETER

CODE: DH-IF-THERMO

- LED luminous display function
- · High sensor quality
- Automatic high temperature warning alarm
- One key operation
- Has a large memory capacity

- Hospitals
- Airports
- Schools
- Mobile screenings
- Home





DISCLAIMER

It is recommended that the local standards and regulations for foot protection, recommendations for selection, use, care and maintenance should be used. This information is a guide for selection only. All footwear is manufactured to statutory and specific tender requirements and should not be modified in any way.

ISO 20345:2011

The standard covers all requirements for safety footwear the understanding of the classifications, categories and other performance requirements will allow the user to select the correct shoe or boot for the intended operation and potential hazards.

CLASSIFICATION OF FOOTWEAR

Footwear made from leather and other materials

All-rubber entirely vulcanised or all-polymeric entirely moulded

MARKING CATEGORY

Category	Class	Performance	
SB	I	Impact & Compression	
S1	I	SB + Closed Seat + A + E	
S1P	1	S1 + P	
S2	1	S1 + WRU	
S3	1	S2 + P + Cleated Outsole	
S4	II	SB + A + E	
S5	II	S4 + P + Cleated Outsole	

TEST REQUIREMENTS

SYMBOL	REQUIREMENTS	PERFORMANCE
SB	Impact resistance (Steel toe cap)	>200 J (Joule)
	Compression test	>15kN
Р	Puncture resistant sole	≥1,100N
С	Electrical resistant	<100 kQ
Α	Anti-static	100 kQ ≤1 000 MQ
1	Electrically insulating footwear	Class 0 or 00
Н	Insulates against heat	Up to 150°C
CI	Insulates against cold	Up to -20°C
E	Energy absorption in heel	≥20J
WR	Water resistant footwear	≤3 cm2
М	Metatarsal protection	> 200J
AN	Ankle protection	>30kN
WRU	Uppers resistant to water penetration	≥60 mins
CR	Cut resistant upper	≥2 5 (Index)
HRO	Heat resistant outsole	Up to 300°C

MARKING FOR SLIP RESISTANCE

SRA	Slip resistance on ceramic tile floor with SLS*
SRB	Slip resistance on steel floor with glycerol
SRC	Slip resistance on ceramic tile floor with SLS* and on steel floor with glycerol

*SLS = Sodium lauryl sulphate solution















HORSE







ABSORBING

HEEL

MIDSOLE







FOOTWEAR



RESISTANT

OUTSOLE





POLYURETHANE

IMPACT S1 SAFETY COMPRESSION & SHOE PUNCTURE

FOOTWEAR

APPROVAL STANDARD





APPROVAL STANDARD



STANDARD









STEEL TOE CAP





RESISTANT

SOLE (SRC)





LEATHER

















ULTECOPLUS **BOOT**

CODE: DF-SK7026 NRCS/9002/217251/0005





























- Conforms to EN ISO 20345:2011, NRCS/9002/217251/0005 as per SANS 20345:2014
- Water resistant Buffalo Buff leather upper
- Steel midsole protects against penetrating surfaces and objects
- Cleated oil & slip resistant outsole, SRC (Slip resistance on ceramic tile floor with NaLS (sodium lauryl sulphate) and on steel floor with glycerine^c)
- Dual density PU (Polyurethane) lightweight outsole and an insole with anti-static technology
- Heat insulation properties on the outsole up to 95° C
- Outsole with energy absorption heel.
- Removable and breathable PU and Memory Foam insole designed for superior comfort
- Impact resistant steel toe cap rated up to 200 \pm 4 Joules
- Scuff cap for extra toe reinforcement & upper protection

- Wider toe cap for extra room and comfort
- Bellows tongue prevents liquids and particulates from entering the boot
- Replacement insoles available (see Pg. 157)

Sizes: 3 - 13

- General use
- Warehouses
- Freight industry
- Mining
- · Engineering
- Construction



ULTECO SHOE























- Conforms to EN ISO 20345:2011, NRCS/9002/217251/0006 as per SANS 20345:2014
- Durable Buffalo Buff leather upper
- Cleated oil & slip resistant outsole, SRC (Slip resistance on ceramic tile floor with NaLS (sodium lauryl sulphate) and on steel floor with glycerine^c)
- Dual density PU (Polyurethane) lightweight outsole and an insole with anti-static technology
- Heat insulation properties on the outsole up to 95° C
- Outsole with energy absorption heel
- Removable and breathable PU and Memory Foam insole designed for superior comfort
- Impact resistant steel toe cap rated up to 200 \pm 4 Joules
- Wider toe cap for extra room and comfort
- Bellows tongue prevents liquids and particulates from entering the boot
- Scuff cap for extra toe reinforcement & upper protection
- Replacement insoles available (see Pg. 157)

3 - 13 Sizes:

Suitable Use:

- · General use
- Warehouse environment
- Freight industry
- Mining
- Engineering
- Construction





NOBUHLE LADIES BOOT

CODE: DF-NOBUHLE NRCS/9002/217251/0238























- Conforms to EN ISO 20345:2011, NRCS/9002/217251/0238 as per SANS 20345:2014
- Durable Buffalo Buff leather upper
- Cleated oil & slip resistant outsole, SRC (Slip resistance on ceramic tile floor with NaLS (sodium lauryl sulphate) and on steel floor with glycerine^c)
- Dual density PU (Polyurethane) lightweight outsole and an insole with anti-static technology
- Heat insulation properties on the outsole up to 95° C
- Outsole with energy absorption heel
- Removable and breathable PU and Memory Foam insole designed for superior comfort
- Impact resistant composite toe cap rated up to 200 \pm 4 Joules

- Metal free lace fastenings
- Wider toe cap for extra room and comfort
- Replacement insoles available (see Pg. 157)

Sizes:

- General use
- Warehouse environment
- Freight industry
- Mining
- Engineering
- Construction







ULTECO

CODE: DF-UBLK

NRCS/9002/217251/0321

























- Conforms to EN ISO 20345:2011, NRCS/9002/217251/0321 as per SANS 20345:2014
- Full grain Buffalo leather upper
- Oil & slip resistant outsole, SRC (Slip resistance on ceramic tile floor with NaLS & on steel floor with glycerine^c)
- Heat insulation properties of the outsole withstands up to 95°C
- Energy absorbing heel
- Removable and breathable PU and Memory Foam insole designed for superior comfort
- Bellows tongue & padded collar for added comfort
- Anti-static removable in-sock
- Steel toe cap is impact resistant up to 200 $\pm\,4J$
- Wider toe cap provides extra room & comfort
- Cleated outsole for additional traction
- Scuff toe over-cap for extra reinforcement
- BASF PU dual density outsole
- Replacement insoles available (see Pg. 157)

Sizes: 3 - 13

Suitable Use:

- General use
- Warehouse environment
- Freight industry
- Mining
- Engineering
- Construction

S1 BOXER BOOT

CODE: SS1020/BOOT NRCS/9002/271251/0004



















- Black leather upper, steel toe cap & lace-up closing
- Injected dual density polyurethane outsole
- Polyurethane tongue & collar
- Non-woven vamp lining
- Mesh quarter lining Non-woven insole
- Mesh & EVA insock

Sizes: 3 - 13

- Ideal as a boot or shoe for contract workers
- General use
- Warehouse environment
- Freight industry





- Conforms to EN ISO 20345:2011, NRCS/9002/217251/XXXX as per SANS 20345:2014
- Made from premium full grain Crazy Horse leather
- Steel midsole protects against penetrating surfaces and objects
- Cleated oil and slip resistant outsole, SRC (Slip resistance on ceramic tile floor with NaLS (sodium lauryl sulphate) and on steel floor with glycerine^c)
- Dual density PU (Polyurethane) lightweight outsole and an insole with anti-static technology
- Heat insulation properties on the outsole up to 95° C
- Outsole with energy absorption heel.
- Removable and breathable PU and Memory Foam insole designed for superior comfort
- Impact resistant steel toe cap rated up to 200 \pm 4 Joules

- Wider toe cap for extra room and comfort
- Replacement insoles available (see Pg. 157)

Sizes: 3 - 13

- General use
- Warehouses
- · Freight industry
- Mining
- Engineering
- Construction



















SPARTICUS GUMBOOT

CODE: DF-SP-STCM

- Slip resistant outsole, SRC (Slip resistance on ceramic tile floor with NaLS and on steel floor with glycerine^c)
- A penetration resistant stainless-steel midsole
- An impact resistant steel toe cap that withstands up to $200 \pm 4 J$, and a compression resistance of 15KN.
- Basic light chemical spray and splash protection and tested to acetic acid at a concentration of 99± 1% as per EN 13832-3:2006
- Reinforced shin, ankle, heel and toe protection
- Energy absorbing heel.
- Anti-static, reducing the chance of electrostatic discharges
- Cleated outsole for additional traction on slippery surfaces
- A broad fitting toe region allowing a comfortable fit for men and ladies feet, especially over long periods of time.

Sizes: 4 - 13

Suitable Use:

- Warehouse environments
- Agriculture
- Freight industry
- Contractors



ARMOUR GUMBOOTS

CODE: DF-ARMOUR

- Slip resistant outsole, SRC (Slip resistance on ceramic tile floor with NaLS and on steel floor with glycerine^c)
- Reinforced shin & ankle protection
- Energy absorbing heel
- Anti-static, reducing the chance of electrostatic discharges
- Oil resistant & cleated outsole
- Average weight: 1.9kgs

Sizes: 4 - 14

Suitable Use:

- **Food Processing**
- **Fisheries**
- Agriculture
- **Janitorial**



SHOVA GUMBOOTS

CODE: DF-GB-GP

- General purpose knee-length PVC gumboot
- High endurance
- Excellent grip & sole support
- Average weight: 2kgs

Sizes: 4 - 13

- Construction
- Agriculture
- Wet environments







GUMBOOTS



NEW

MIGHTY NITE GUMBOOT

CODE: DF-GB-MN

- Knee-length PVC / Nitrile gumboots
- Anti-bacterial, hygienic & lightweight
- Slip resistant outsole, SR (Slip resistance on ceramic tile floor with NaLS and on steel floor with glycerine^c)
- · Energy absorbing heel
- · Anti-static, reducing the chance of electrostatic discharges
- An oil resistant and cleated outsole providing additional traction on slippery surfaces
- · A wide toe region for hours of comfort
- · Reinforced shin and ankle protection
- Easy to pull off tab construction
- Average weight: 1.7 1.9kg's (size dependant)

Sizes: 4 - 13

Suitable Use:

- Food processing
- **Butcheries**
- **Fisheries**
- Agriculture

















LADIES LITE GUMBOOT

CODE: DF-GB-LL

- Calf-length PVC / Nitrile gumboots
- Anti-bacterial, hygienic & lightweight
- Slip resistant outsole, SR (Slip resistance on ceramic tile floor with NaLS and on steel floor with glycerine^c)
- · Energy absorbing heel
- Anti-static, reducing the chance of electrostatic discharges
- An oil resistant and cleated outsole providing additional traction on slippery surfaces
- A wide toe region for hours of comfort
- Reinforced shin and ankle protection
- Easy to pull off tab construction
- Average weight: 1.0 1.2kg's (size dependant)

Sizes: 3 - 9

- Food processing
- **Butcheries**
- **Fisheries**
- Agriculture





















FLAME RETARDANT SOCKS

CODE: DF-9162-CH-L



- · Ribbed cuff for secure fit
- Reinforced heel & toe for durability
- Blister resistant
- Thermally balanced & odour free
- Will not burn when exposed to heat & flame 80% Wool, 15% Nylon, 4% Lycra, 1% Elastane Aflammit® ZR treated yarn

Sizes: Large (8 - 11)

Suitable Use:

- · Petroleum service industry
- · Petrochemical industry
- Oil & gas industry
- Electrical & gas utility
- · Steel mills
- Fighter pilots





BLACK



NAVY BLUE

ANTI-STATIC SOCKS

CODE: DF-9161

- 64% Cotton, 9% Polyester, 4% Silver Yarn,
 21% Elastane, 2% Polyamide
- Designed to safely conduct static build-up away from workers & equipment
- Anti-bacterial fibres
- Ribbed cuff for secure fit
- Elasticated arch & padded sole for extra comfort

Sizes:

- Medium (4 7)
- Large (8 11)

- Manufacturing (incl. computer equipment)
- Refineries





BLACK



CHARCOAL



NAVY BLUE



KHAKI

WORKWEAR SOCKS

CODE: DF-9160

- 62% Cotton, 27% Elastane, 9% Polyester
 2% Polyamide
- · Reinforced heel & toe for durability
- Ribbed cuff for secure fit
- Cushioned feet & sole for comfort
- Cotton & Polyester blend enhances comfort & breathability
- Perfect for all-day use

Sizes:

- Medium (4-7)
- Large (8 11)

Suitable Use:

- Warehousing
- Janitorial
- Gardening
- General use



BLACK



NAVY BLUE

NON-ABRASIVE SOCKS

CODE: DF-8055

- 15% Mohair, 29% Polyamide, 16% Elastane,
 25% Cotton, 15% Acrylic
- Designed for use with steel-toe & heavy work boots
- Mohair blister resistant wool eliminates blisters & hotspots
- · Ribbed cuff for secure fit
- · Reinforced heel and toe for durability
- Keeps feet free from moisture & thermally balanced preventing odour & bacteria build up

Sizes

- Medium (4 7)
- Large (8 11)

- Construction
- Agriculture
- Mining



South African Institute of Occupational Safety and Health



www.saiosh.co.za



Saiosh is recognised by the South African Qualifications Authority (SAQA) as the Professional Body to register Occupational Health and Safety Professionals in South Africa in terms of the NQF Act, Act 67 of 2008.

We believe that all employees in any work environment are entitled to maximum safety protection and that employers should not have to compromise on the quality of the PPE products they provide for their staff.

KZN HEAD OFFICE Unit 1, 1 Blase Road New Germany, 3610 South Africa

E. sales@dromex.co.za T. +27 (0)31 713 1960 JOHANNESBURG 7 Mirage Road, Bedfordview, Germiston, 2008 South Africa

T. +27 (0)11 450 0444

CAPE TOWN
Unit A26, Block 1
Northgate Office Park
Section Road, Brooklyn
Cape Town, 7405
South Africa
T. +27 (0)21 224 0935

PORT ELIZABETH Unit F7-F10 Circular Business Park 31 Circular Drive Port Elizabeth, 6070 South Africa T. +27 (0)41 250 0040



OCTOBER 2023

Dromex® and all associated logos are registered trademarks. Dromex® reserves the right to make changes without further notice to any products herein to improve function, design or reliability and validity. Dromex® does not assume any liability arising out of the application or use of any product described herein.

Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner.